



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 23952KEMW33C3, Spherical Roller Bearings - Brass Cage

Spherical bearings are designed to manage high radial loads even when misalignment, poor lubrication, contamination, extreme speeds or critical application stresses are present.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Design Unit	Metric
d - Bore	260 mm
Bore_Taper	1/12
Cage Type	EM
Cage Material	Brass
Superseded Part	23952KYMW33C3

Dimensions



D - Outer Diameter

360 mm
14.1732 in

B' - Inner Ring Width	75 mm 2.9528 in
B - Outer Ring Width	75 mm 2.9528 in

Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius¹	2 mm 0.080 in
r - Outer Ring "To Clear" Radius²	2 mm 0.08 in
da - Inner Ring Backing Diameter	284.000 mm 11.2000 in
Da - Outer Ring Backing Diameter	339 mm 13.3000 in

Basic Load Ratings

C0 - Static Radial Rating	1860000 N 419000 lbf
C1(2) - Dynamic Radial Rating (Two-Rows)	1120000 N 251000 lbf

Factors

e - ISO Factor³	0.18
Y0 - ISO Factor⁴	3.65
Y1 - ISO Factor⁵	3.74
Y2 - ISO Factor⁶	5.56
Reference Thermal Speed Rating (Grease)	1200 rpm

Reference Thermal Speed Rating (Oil)⁷	1400 rpm
---	----------

Cg - Geometry Factor⁸	0.1103
---	--------

¹ Maximum housing fillet radius that bearing corners will clear.

² Maximum shaft fillet radius that bearing corners will clear.

³ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.


⁴ These factors apply for both inch and metric calculations. See engineering

⁵ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁶ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁷ See thermal speed ratings in the engineering section.

⁸ Geometry constant for Lubrication Life Adjustment Factor a3l.



METRIC UNITS

Number of Rollers Per Row	33
ISO Factor e	0.18
ISO Factor Y0	3.65
ISO Factor Y1	3.74
ISO Factor Y2	5.56
Bearing Weight	22.8 kg
Cage Type	EM
Cage Material	Brass
Bore Taper	1/12



THE TIMKEN COMPANY

NORTH CANTON, OHIO USA

23952KEMW33C3
SRB ASSEMBLY

Dynamic Radial Rating (Two Rows)	1120000	N
Static Radial Rating	1860000	N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY