



NTN BEARING CORPORATION OF AMERICA

Head Office

1600 E. Bishop Court, P.O. Box 7604

Mount Prospect, IL 60056-7604, U.S.A.

Phone: 847-298-7500


Fax: 847-699-9744

Toll Free: 800-323-2358

Email: mkt@ntnamerica.com

Website: www.ntnamericas.com

Item # UCT216D1, Take-Up Unit, Cast Housing, Set Screw, UCT Type



[Order Now](#) | [Technical Specifications](#) | [Dimensional Specifications](#) | [Specifications](#)

Order Now

Ordering Options

FIND A DISTRIBUTOR

CONTACT NTN CUSTOMER SUPPORT SPECIALIST

ORDER THROUGH NTN DOL (AUTHORIZED DISTRIBUTORS ONLY)


Technical Specifications

Type

Take-Up Unit

Bearing Type	Ball Bearing
Locking Device	Set Screw
Seal Type	Contact
Seal Material	Nitrile Rubber
Bearing Number	UC216D1
Housing Number	T216D1
Housing Material	Cast Iron
Performance	Light Duty
Dynamic Load Rating	16299 lbf 72500 N 72.50 kN
Static Load Rating	11915 lbf 53000 N 53.00 kN
Rotational Speed [Max]	2000.0 RPM
Weight	18.081 lb 8.200 kg
Operating Temperature Range	-40 to 250 °F -40 to 120 °C
Lubrication	Relubricatable

Dimensional Specifications



Take-Up Unit, Cast Housing, Set Screw, UCT Type - Dimensions

d	3.1500 in 80.000 mm
L	9.2500 in 235.0 mm
H	7.2500 in 184.0 mm
H1	6.5000 in 165.0 mm
H2	4.3750 in 111.0 mm
L1	5.5000 in 140.0 mm
L2	0.9062 in 23.0 mm
L3	4.7500 in 121.0 mm
N	1.6250 in 41.0 mm
N1	1.2500 in 32.0 mm
N2	2.7500 in 70.0 mm
A	2.7500 in 70.0 mm
A1	1.0236 in 26.0 mm
A2	2.0000 in 51.0 mm
r	3.7500 in 95.0 mm
B	3.2520 in 82.600 mm
S	1.3110 in 33.300 mm

F

0.3740 in
9.500 mm

Specifications

Lubrication

Outer Ring

Ball Material

Through Hardened

Outside Diameter

5.5120 in
140.000 mm

Outside Diameter

5.5120 in
140.000 mm

Bore Type

Cylindrical

Outside Ring Width

1.3780 in
35.000 mm

Inside Ring Width

3.2520 in
82.600 mm

Clearance

CN

Cage Material

Pressed Steel

Precision Rating

ISO Class 0

Radial Dynamic Load Rating

16299 lbf
72500 N

Radial Static Load Rating

11915 lbf
53000 N

Rotational Speed [Max]-Grease

2000 RPM