



Image may differ from product. See specification for details.

## WSTU 014-TF

Take-up ball bearing unit with composite or cast metal housing

Take-up ball bearing units consisting of an insert bearing mounted in a composite or cast metal housing. The units are typically mounted in take-up frames and adjusted by an adjustment screw. In addition to being part of a unit, some take-up housings for insert bearings are available as separate components. The SKF assortment includes take-up ball bearing units compliant with several industrial standards, as required by many industrial applications.

- Ready to mount
- Lubricated and sealed bearings
- Quick locking on the shaft
- Large variety of housing shapes, housing materials, and locking methods
- Concentric locking options for high speeds and low vibration

## Overview

### Dimensions

|                       |           |
|-----------------------|-----------|
| Shaft diameter        | 22.225 mm |
| Housing overall width | 31.8 mm   |
| Bearing width, total  | 34.1 mm   |

### Performance

|                           |                                        |
|---------------------------|----------------------------------------|
| Basic dynamic load rating | 14 kN                                  |
| Basic static load rating  | 7.8 kN                                 |
| Limiting speed            | 7 000 r/min                            |
| Note                      | Limiting speed with shaft tolerance h6 |

### Properties


|                               |                                |
|-------------------------------|--------------------------------|
| Housing type                  | Take-up                        |
| Retaining feature, inner ring | Set screws                     |
| Bore type                     | Cylindrical                    |
| Rubber seating ring           | Without                        |
| Material, housing             | Cast iron                      |
| Material, bearing             | Bearing steel                  |
| Coating                       | Without                        |
| Sealing, bearing              | Seal and flinger on both sides |
| Sealing type                  | Contact, standard              |
| Sealing, unit                 | Optional end cover             |
| Lubricant                     | Grease                         |
| Relubrication hole            | With                           |
| Grease fitting                | With                           |


### Logistics

|                    |             |
|--------------------|-------------|
| Product net weight | 0.906 kg    |
| eClass code        | 23-05-16-01 |
| UNSPSC code        | 31171536    |

Technical specification

|                          |                                    |
|--------------------------|------------------------------------|
| Compliance with standard | North American standard            |
| Purpose specific         | For material handling applications |
| Material, housing        | Cast iron                          |
| Sealing, bearing         | Seal and flinger on both sides     |
| Sealing type, bearing    | Contact, standard                  |
| Sealing, unit            | Optional end cover                 |
| Coating                  | Without                            |





## Dimensions

|                |            |                                                                             |
|----------------|------------|-----------------------------------------------------------------------------|
| d              | 22.225 mm  | Bore diameter                                                               |
| d <sub>1</sub> | ≈ 33.74 mm | Shoulder diameter of inner ring                                             |
| A              | 31.8 mm    | Overall width                                                               |
| A <sub>1</sub> | 13.5 mm    | Width of piloting groove                                                    |
| A <sub>2</sub> | 23.8 mm    | Width of flange in which piloting grooves are provided                      |
| A <sub>5</sub> | 20.5 mm    | Standout of end cover                                                       |
| B              | 34.1 mm    | Width of inner ring                                                         |
| B <sub>4</sub> | 5 mm       | Distance from locking device side face to thread centre                     |
| H              | 88.9 mm    | Overall height                                                              |
| H <sub>1</sub> | 76.2 mm    | Distance between bottoms of piloting grooves                                |
| H <sub>2</sub> | 50.8 mm    | Height of attachment end                                                    |
| L              | 96.8 mm    | Overall length                                                              |
| L <sub>1</sub> | 61.9 mm    | Distance from attachment end face to centre line of spherical seat diameter |
| L <sub>2</sub> | 10.3 mm    | Length attachment end                                                       |
| L <sub>3</sub> | 50.8 mm    | Length of piloting groove                                                   |
| N              | 17.5 mm    | Diameter of attachment bolt hole                                            |

|                      |         |                                                          |
|----------------------|---------|----------------------------------------------------------|
| <b>N<sub>1</sub></b> | 15.9 mm | Length of attachment slot                                |
| <b>N<sub>2</sub></b> | 31.8 mm | Height of attachment slot                                |
| <b>s<sub>1</sub></b> | 19.8 mm | Distance from locking device side face to raceway centre |

## THREADED HOLE

|                      |            |                                        |
|----------------------|------------|----------------------------------------|
| <b>R<sub>G</sub></b> | 1/8-27 NPT | Housing thread for the grease fitting  |
| <b>R<sub>1</sub></b> | 0.3 mm     | Axial position of the housing thread   |
| <b>R<sub>α</sub></b> | 30 °       | Angular position of the housing thread |

## GREASE FITTING

|                       |            |                                           |
|-----------------------|------------|-------------------------------------------|
| <b>D<sub>N</sub></b>  | 6.579 mm   | Diameter of head sphere of grease fitting |
| <b>SW<sub>N</sub></b> | 11.113 mm  | Hexagonal key size for the grease fitting |
| <b>G<sub>N</sub></b>  | 1/8-27 NPT | Thread of grease fitting                  |

## Calculation data

|                           |                      |                                        |
|---------------------------|----------------------|----------------------------------------|
| Basic dynamic load rating | <b>C</b>             | 14 kN                                  |
| Basic static load rating  | <b>C<sub>0</sub></b> | 7.8 kN                                 |
| Fatigue load limit        | <b>P<sub>u</sub></b> | 0.335 kN                               |
| Limiting speed            |                      | 7 000 r/min                            |
|                           |                      | Limiting speed with shaft tolerance h6 |

## Mounting information

|                                             |                      |            |
|---------------------------------------------|----------------------|------------|
| Set screw                                   | <b>G<sub>2</sub></b> | 1/4-28 UNF |
| Hexagonal key size for set screw            |                      | 3.175 mm   |
| Recommended tightening torque for set screw |                      | 4 N·m      |

## Tolerances and clearances

---

The values depend on the included bearing:

- Bore diameter tolerance → [table 1](#)
- Radial internal clearance → [table 2](#)
- Recommended fit → [table 3](#)
- Shaft tolerance → [table 4](#)

Compatible products

Component

---

Insert bearing with set screw locking and extended inner ring

[YAR 205-014-2F](#)

Recommended product

---

End cover for bearing units

[ECY 205](#)

More Information

| Product details                                                      | Engineering information                                                                                  | Tools                                        |
|----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------|
| <a href="#">Take-up units to ISO standards</a>                       |                                                                                                          | <a href="#">SKF Product select</a>           |
| <a href="#">Take-up units to North American standards</a>            | <a href="#">Principles of ball bearing units selection and application - Download catalogue (4.9 MB)</a> | <a href="#">Bearing Frequency Calculator</a> |
| <a href="#">Take-up units to Japanese Industrial Standards (JIS)</a> | <a href="#">Principles of selecting mounted bearing solutions</a>                                        |                                              |
| <a href="#">Take-up units, not standardized (SKF Food Line)</a>      | <a href="#">Bearing failure and how to prevent it</a>                                                    |                                              |
| <a href="#">Permissible misalignment</a>                             |                                                                                                          |                                              |
| <a href="#">Locating/non-locating support</a>                        |                                                                                                          |                                              |
| <a href="#">Loads</a>                                                |                                                                                                          |                                              |
| <a href="#">Temperature limits</a>                                   |                                                                                                          |                                              |
| <a href="#">Permissible speed</a>                                    |                                                                                                          |                                              |
| <a href="#">Lubrication</a>                                          |                                                                                                          |                                              |
| <a href="#">Mounting and dismounting</a>                             |                                                                                                          |                                              |
| <a href="#">Ordering information</a>                                 |                                                                                                          |                                              |
| <a href="#">Designation system</a>                                   |                                                                                                          |                                              |



# Terms of use

By accessing and using this website / app owned and published by AB SKF (publ.) (556007-3495 · Gothenburg) ("SKF"), you agree to the following terms and conditions:

## **Warranty Disclaimer and Limitation of Liability**

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app.

Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service.

Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

## **Third Party Services**

When viewing YouTube content via the SKF website(s) (i.e. using [YouTube API Services](#)), you agree to be bound by the [YouTube Terms of Service](#).

## **Copyright**

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third parties.

This website /app includes certain images used under license from Shutterstock, Inc.

## **Trademarks and Patents**

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

## **Changes**

SKF reserves the right to make changes or additions to this website / app at any time.