



## SPECIFICATION SHEET

Ultrasonic Model VB3.5VT Vibratory Deburring and Finishing Bowl Machine. Specified and described below. Wet or Dry applications.

SPECIFICATIONS	
Bowl Diameter	32
Channel Width	11
Capacity	3.5 Cu. Ft.
Load Capacity	600 Lbs.
Machine Height	38"
Machine Length	36"
Machine Width	32"
Shipping Weight	950 Lbs.
Lining: 80 Durometer	3/4 "
Input Voltage	110/1/60
Drive Unit: 1.75 HP	1800 Rpm
Specifications subject to change	



VB3.5 with Variable Speed Drive, On Off Timer Switch with corded plug Included with Machine


## STANDARD FEATURES

- CAST PREMIUM POLYURETHANE LINING
- DIRECT DRIVE MOTOR W/ ADJUSTABLE WEIGHTS
- HEAVY DUTY STEEL PLATE FABRICATED BOWL AND BASE
- URETHANE MOUNTED COIL SPRING SUSPENSION
- AC VARIABLE SPEED DRIVE W/ DIGITAL DISPLAY
- 110 VOLT TIMER SWITCH WITH CORDED PLUG STAND MOUNTED
- DISCHARGE DOOR AND REMOVABLE DRAIN
- LUBRICATED FOR LIFE MOTOR
- SOLUTION INPUT VALVE
- RECEPTACLE FOR SOLUTION PUMP
- PAINT: TWILIGHT GRAY INDUSTRIAL ENAMEL
- 1 YEAR WARRANTY

**DIRECT DRIVE SERIES** • features a Heavy Duty Vibratory Motor with easily adjustable weights. This unique design feature eliminates belts and pulleys and supplies 100 % power to the Tub. Requires 50% less HP resulting in huge electrical operation cost savings.



Adjustable Flywheels and Weights



Direct Drive Motor System  
100% power to the Bowl  
50% less HP required than belt drive machines  
Lubricated for Life  
No Maintenance required

ADDITIONAL STANDARD FEATURES



Variable Speed, On Off  
Switch , Receptacle for  
solution pump and  
corded plug included

AVAILABLE OPTIONS

ST15FS Filtration System ▪ Includes 15 Gallon Tank with Cover, weirs, Filter Bag & 110-volt Recirculation Pump. Polyethylene Tank ID is 20" L x 15" W x 12" High.

