



ULTRAMATIC EQUIPMENT CO.

Vibratory Finishing Equipment Technology Since 1959



Ultramatic Model **P3 SE** Vibratory Deburring and Finishing Machine, steel fabricated heavy-duty construction specified and described below.

Direct Drive Series features a Heavy-Duty Vibratory Motor with easily adjustable weights. This unique design feature eliminates belts and pulleys and supplies 100 % power to the Tub. Requires 50% less HP resulting in huge electrical operation cost savings and low decibel levels 80dB.

SPECIFICATIONS	
Tub Length Inside after lining	28.5"
Tub Width Inside after lining	15"
Total Capacity	3 Cu Ft
Machine Height	40"
Machine Length	36"
Machine Width	32"
Shipping Weight	775 Lbs.
Lining: 80 Durometer	5/8 "
Input Voltage	110
Drive Unit Centrifugal Force : 1570 lbs.	1800 Rpm
Specifications subject to change	



STANDARD FEATURES

OFFSET **DIRECT DRIVE** FOR SUPERIOR FINISHING RESULTS
1.1 HP DIRECT DRIVE WITH EASY ADJUSTABLE WEIGHTS
AC VARIABLE SPEED DRIVE W/ DIGITAL DISPLAY
110 VOLT TIMER SWITCH & RECEPTACLE W/ CORDED PLUG
SUPER QUIET METAL BASE WITH HINGED SOUND COVER
COIL SPRING SUSPENSION WITH URETHANE MOUNTS
CASTERS WITH LOCK FOR PORTABILITY
PAINT: BLACK INDUSTRIAL ENAMEL / TWILIGHT GRAY

PREMIUM CAST POLYURETHANE
MEDIA DISCHARGE DOOR
REMOVABLE DRAIN WITH HOSE
ADJUSTABLE AMPLITUDE
COMPOUND SPRAY PIPING
RECIRCULATION PUMP AND TANK
LUBRICATED FOR LIFE
ONE YEAR WARRANTY

- FOB: Addison, IL.

P3 SE STANDARD FEATURES



Variable Speed, Timer Switch , Receptacle for solution pump and corded plug included



Hinged Sound Reduction Tub Cover



Tank and pump



Direct Drive Motor
Adjustable Flywheels
and Weights
Lubricated for Life

OPTIONAL EQUIPMENT

- ST15FS Filtration System
- Process Timer
- Tub Divider



ST15FS Option