

Model	GEO-LFPHVS-10-50						
Units NO	4	5	6	7	8	9	10
Usable Capacity	10KWH	12.5KWH	15KWH	17.5KWH	20KWH	22.5KWH	25KWH
Nominal Voltage	204.8V	256V	307.2V	358.4V	409.6V	460.8V	512V
Voltage Range	182.4V-224.64V	228V-280.8V	273.6V-336.96V	319.2V-393.12V	364.8V-449.28V	410.4V-505.44V	456V-561.6V
MAX.Charge & Discharge Current	30A						
Rated Charge & Discharge Current	25A						
Rated Charge & Discharge Power	5.12KW	6.4KW	7.68KW	8.96KW	10.24KW	11.52KW	12.8KW
MAX.Units in Parallel	6 Groups						
DOD	≥95%						
Cooling	Natural						
Communication	CAN&RS485&RS232						
Ingress Protection	IP56						
Cycle Life	≥6000@25°C, 80%DOD						
Working Temperature Range	Discharge:-20°C to +65°C, Charge:+0°C to +65°C						
Net Weight(KG)	138KG	168KG	198KG	228KG	258KG	288KG	318KG
Product Dimension(MM)	515*480*770	515*480*895	515*480*540	515*480*1020	515*480*1145	515*480*1270	515*480*1520