


nVent LENTON Mechanical Anchors

Meets international standards, including BS EN 1992-1-1, DIN EN 1992-1-1, NFA-35-020, ACI®318, and ASTM® A970.



The nVent LENTON Terminator provides an alternative to hooked rebar, or an anchor or stop nut for rebar passing through a pile plank or structural steel element. The front face of the coupler is generously designed to carry the full tension load of the rebar when the anchor is bearing against concrete or structural steel.

The A2D6 Terminator (not shown) is threaded on both sides for future extension work and provides the same anchorage benefits as the D6 and D16. This coupler is available in North America only. Contact nVent for more information.

- A** = large diameter
- B** = length of coupler body/
bar engagement
- E** = length of small step
- F** = small diameter


TERMINATOR - D14

STANDARD IN THE AMERICAS*, EUROPE, THE MIDDLE EAST AND AFRICA

Rebar Size Designation mm	Part No.	"A" mm	"B" mm	"E" mm	"F" mm	Weight Kg
10	EL10D14	35	18	-	-	0.13
12	EL12D14	45	18	-	-	0.22
14	EL14D14	45	21	-	-	0.25
16	EL16D14	55	24	-	-	0.42
18	EL18D14	60	29	-	-	0.61
20	EL20D14	65	35	-	-	0.84
22	EL22D14	70	37	-	-	1.04
25	EL25D14	80	40	-	-	1.45
28	EL28D14	95	42	25	80	1.76
30	EL30D14	95	52	25	80	2.26
32	EL32D14	105	45	25	80	2.14
34	EL34D14	110	55	25	80	2.94
36	EL36D14	115	52	25	80	2.84
38	EL38D14	120	53	25	80	3.12
40	EL40D14	130	58	26	58	3.41
43	EL43TD14	150	67	34	61	4.73
50	EL50TD14	160	71	33	77	6.38
57	EL57TD14	190	84	41	80	9.72

*Available in select regions of U.S.

Meets BS EN 1992-1-1, IBC®, AS3600, ACI®318, and ASTM A970.



TERMINATOR - D6

STANDARD IN THE AMERICAS, ASIA AND AUSTRALIA

Inch lb	Rebar Size Designation			Part No.	"A"		"B"		"E"		"F"		Weight	
	Metric	Canadian	Soft Metric		in	mm	in	mm	in	mm	in	mm	lb	kg
4	12 mm	10M	13	EL12D6	1-3/8	35	9/16	14	-	-	-	-	0.2	0.09
5	16 mm	15M	16	EL16D6	1-1/2	38	7/8	22	-	-	-	-	0.4	0.18
6	20 mm	20M	19	EL20D6	1-7/8	48	1-1/8	29	-	-	-	-	0.8	0.36
7	22 mm	-	22	EL22D6	2	51	1-1/4	32	-	-	-	-	1.0	0.45
8	25 mm	25M	25	EL25D6	2-1/4	57	1-3/8	35	-	-	-	-	1.3	0.59
9	28 mm	30M	29	EL28D6	2-3/4	70	1-1/2	38	-	-	-	-	2.2	1.00
10	32 mm	-	32	EL32D6	3	76	1-9/16	40	-	-	-	-	2.7	1.22
11	36 mm	35M	36	EL36D6	3-1/4	83	1-11/16	43	-	-	-	-	3.4	1.54
-	40 mm	-	-	EL40D6	3-3/4	95	2-1/2	64	1	25	3	76	5.5	2.49
14	43 mm	45M	43	EL43TD6	4	102	2-1/8	54	1	25	3	76	4.9	2.22
-	50 mm	-	-	EL50TD6	4-1/2	114	2-9/16	65	1	25	3	76	7.1	3.22
18	57 mm	55M	57	EL57TD6	5-1/8	130	2-3/4	70	1	25	3	76	9.8	4.45

NOTE: Thread does not need to be flush with end of Terminator. Thread may be +/- 2 threads from backside of coupler.

Diameter exceeds 5x bar area requirements of AC347 & ACI.

Bar dimensions and weights listed may vary by region. Coupler sizes not shown on these

pages are available by special order. Contact your nVent representative for more information on special sizes. Article numbers used in Europe, Middle East, Africa and Asia exclusively.