Roof Quote/Order Form





200mm-600mm in 100mm increments

Job Ref:						Take a photo of you completed form, so the QR code and upload the photo o your form.	
Company Name:			Contact Name:				
Delivery Address:							
WIDTH:	PROJECTION:	PITCH:	0			window vents Small (550 x 780) Large (780 x 980) Other Manual Electric* Solar* *Active	
		Please spec	ify distance b	oof vents and gla etween roof hips e include a frame	is applicable	GLASS Blue Neutral Clear Other Glass Width (800mm max)	
Shingles Raven Titanium Grey Rustic Brown Bramble Brown Rustic Red Smoked Oak Rustic Terracott LiteSlates Min pitch 12 °	Building Control Yes No Gutter and Downpipe Please note your ThermaCore Warm Roof will be supplied with Ogee gutter profile and round downpipe. Gutter Colour White Anthracite Grey Black Caramel Brown				Fas	12.5mm Plasterboard Supplied None Fascia Colour White Black Rosewood Anthracite Grey	
Slate Sunset Ash Amethyst Oak Sunshine Charcoal	I acknowledge it is my responsibility to make sure the existing structure is suitable to support all lateral and vertical loads and to contact building control to issue any required building warrant. I acknowledge that the manufactureres can not be responsible for any products not fitted in accordance with their installation guide. Signed:				Exte	External Soffit 150mm Other Internal Soffitmm	

Send us your form

Take a photo of your completed form, scan the QR code and upload the photo of your form.

We handle all building control matters inhouse, so if your project requires submission to building control, just let us know - we'll take care of everything.





Britmet Shingle



Titanium Grey



Bramble Brown



Rustic Brown



Rustic Terracotta



Raven



Smoked Oak



Rustic Red

Britmet LiteSlate



Amethyst



Ash



©a[k



Sunshine



Charcoal




Sunset



Slate

150mm External Soffit

Fascia overhang kit option allows for external recessed lighting in soffit board





Low Pitch Roof Sheets

Low pitch option for Lean-to roofs.



Glass Pamals

BLUE

CLEAR

NEUTRAL



Maximum width - 800mm

Standard Specification: Low-e, Self clean, 1.2 W/m2K U-Value