

TECHNICAL DATA SHEET

ORIANT- RACER MIN SAE 20W50 API SL

Description and Application :

Oriant Racer Min SAE 20W50 API SL – is a premium quality, multi grade Gasoline engine oil and superior detergent type lubricants meeting the highest API performances, which is suitable for all passenger cars and light duty vehicles. It can be used in all 4-stroke gasoline engines.

Main Benefits:

- Excellent sludge and oxidation resistance.
- Low volatility and evaporation loss.
- Reduce fuel consumption.
- Superior cold start performance and efficient cold engine lubrication.

Specifications:

API SL
Meets performance:
ACEA A3/B4 (2008)
MB 229.1

Typical Characteristics

Sr. No	Test Parameters SAE Viscosity Grade	Test Method	Typical S A E 20W50
1	Appearance	Visual	C&B*
2	Density @ 15°C gm/cm ³	ASTM D1298	0.869
3	Viscosity Index	ASTM D2270	130
4	Viscosity @ 100°C (cSt)	ASTM D 445	18.25
5	Pour Point °C	ASTM D 97	-27
6	Flash Point (COC) °C	ASTM D 92	246
7	T.B.N mg KOH/gm	ASTM D 2896	7

*C&B = Clear and Bright

The above figures are typical of those obtained with normal production tolerance and do not constitute specification



C.C.M : 104011218404 VAT.No : 310140579100003 C.R : 1011014860

www.STLOP.com

عضوية الغرفة التجارية : ١٠٤٠١١٢١٨٤٠٤ الرقم الضريبي : ٣١٠٠١٤٠٥٧٩١ س.ت : ١٠١١٠١٤٨٦٠

Info@saudilubeoil.com

Head Office HHC Riyadh , Saudi Arabia P.O. Box 1192 Alkharj Sales : +966505223838 Customer service : +966505290044

المكتب الرئيسي الرياض _ المملكة العربية السعودية صندوق البريد : ١٩٩٢ الخرج المبيعات : ٢٨٣٨٢٥-١٦٦٥+ خدمة العملاء :٤٤-١٥٥٥-١٩٦٩+