

# TECHNICAL DATA SHEET ORIANT COOLANT 50% (Antifreeze)

#### **DESCRIPTION :**

**ORIANT COOLANT 50% is** formulated from mono-ethylene glycol (MEG) and recommended for use in liquid cooling systems of automotive and industrial gasoline and diesel engines. It is available in various concentrations ready for use. It is harmless to rubber and does not foam or clog radiators.

### **APPLICATIONS :**

ORIANT COOLANT protects cooling systems of gasoline and diesel engines against rust in all seasons. It provides ideal cooling, effective protection against corrosion and scale deposit formation in the cooling systems year-round, resulting in longer radiator life.

### **BENEFITS:**

- High boiling point gives better cooling performance in high temperature conditions.
- Excellent anti-foam properties.
- Protects the radiator against rust & corrosion.
- Compatible with ordinary summer coolant.
- Protection against excessive evaporation.
- Provides year-round cooling properties.

## **MEETS PERFORMANCES :**

BS6580 ASTM D3306

Complies with most engine manufacturer's requirements to fulfill radiator performances.

## **Typical Characteristics**

Sr. No	Test Parameters	Test Method	Typical
1	Specific Gravity 20°C	ASTM D1298	1.065
2	Colour	VISUAL	GREEN
3	РН	ASTM D 1287	8

#### \*C&B = Clear and Bright

The above figures are typical of those obtained with normal production tolerance and do not constitute specifications.



C.C.M : 104011218404 VAT.No : 310140579100003 C.R : 1011014860

www.STLOP.com

عضوية الغرفة التجارية : ١٠٤٠١١٢١٨٤٠٤ الرقم الضريبي : ٣١٠١٤٠٥٧٩١٠٠٠٠٣ س.ت : ١٠١١٠١٤٨٦٠

Info@saudilubeoil.com

Head Office HHC Riyadh , Saudi Arabia P.O. Box 1192 Alkharj Sales : +966505223838 Customer service : +966505290044

المكتب الرئيسي الرياض \_ المملكة العربية السعودية صندوق البريد : ١٩٩٢ الخرج المبيعات : ٢٨٣٨٢٥-١٦٦٥+ خدمة العملاء :٤٤-١٥٥٥-١٩٦٩+