AL Kharj Industrial City _ Kingdom Saudi Arabia



TECHNICAL DATA SHEET

ORIANT ATF DEX III H

Description and Application :

ORIANT ATF DEX III H is a Transmission fluid, designed for use in modern automatic gearboxes, where GM Dexron or Ford Marcon specifications are quoted.

ATF DEX III H can also be used in most power shift transmissions, power steering and hydraulic units.

Main Benefits:

- Exceptional low temperature fluidity.
- Excellent resistance to oxidation and high thermal stability.
- Durability of friction characteristics and wear protection.
- Protection against rust and corrosion, and good seal compatibility.
- Compatibility with new technologies, such as band clutches and new clutch plate materials.
- ATF DEX III does not contain sperm oil.

Meets Performance :

ATF DEX III meets: TASA to DEXRON III H (GM 6297M/Opel/Vauxhall). Ford MERCON (M2C-185A) It meets the requirement of Allison C4

Typical Characteristics:

Sr. No	Test Parameters	Test Method	Typical
1)	Appearance	Visual	C&B*
2)	Density @ 15°C gm/cm3	ASTM D1298	0.858
3)	Viscosity Index	ASTM D2270	170
4)	Viscosity @ 100°C (cSt)	ASTM D 445	7.8
5)	Pour Point °C	ASTM D 97	-42
6)	Flash Point (COC) °C	ASTM D 92	220

*C&B = Clear and Bright

The above figures are typical of those obtained with normal production tolerance and do not constitute specifications.



C.C.M : 104011218404 VAT.No : 310140579100003 C.R : 1011014860

www.STLOP.com

عضوية الغرفة التجارية : ١٠٤٠١١٢١٨٤٠٤ الرقم الضريبي : ٣١٠٠١٤٠٥٧٩١ س.ت : ١٠١١٠١٤٨٦٠

Info@saudilubeoil.com

Head Office HHC Riyadh , Saudi Arabia P.O. Box 1192 Alkharj Sales : +966505223838 Customer service : +966505290044

المكتب الرئيسي الرياض _ المملكة العربية السعودية صندوق البريد : ١٩٩٢ الخرج المبيعات : ٢٨٣٨٢٥-١٦٦٥+ خدمة العملاء :٤٤-١٥٥٥-١٩٦٩+