

TECHNICAL DATA SHEET

ORIENT- RACER MIN SAE 15W40 API SL

Description and Application :

Oriant Racer Min SAE 15W40 API SL – is a premium quality, multi grade Gasoline engine oil and superior detergent type lubricants meeting the highest API performances, which is suitable for all passenger cars and light duty vehicles. It can be used in all 4-stroke gasoline engines.

Main Benefits:

- ✚ Excellent sludge and oxidation resistance.
- ✚ Low volatility and evaporation loss.
- ✚ Reduce fuel consumption.
- ✚ Superior cold start performance and efficient cold engine lubrication.

Specifications:

- ✚ API SL

Meets performance:

- ✚ ACEA A3/B4 (2008)
- ✚ MB 229.1

Typical Characteristics

Sr. No	Test Parameters SAE Viscosity Grade	Test Method	Typical SAE 15W40
1	Appearance	Visual	C&B*
2	Density @ 15°C gm/cm ³	ASTM D1298	0.860
3	Viscosity Index	ASTM D2270	132
4	Viscosity @ 100°C (cSt)	ASTM D 445	15.23
5	Pour Point °C	ASTM D 97	-30
6	Flash Point (COC) °C	ASTM D 92	240
7	T.B.N mg KOH/gm	ASTM D 2896	6.33
8	Apparent Viscosity@ -20°C cp	ASTM D 5293	6850
9	Foaming Tendency / Stab, Seq II	ASTM D 892	20/0

*C&B = Clear and Bright

The above figures are typical of those obtained with normal production tolerance and do not constitute specification