





# State-of-the-art technology for conclusive inspections





# The new VTec X – Quality, made in Germany

The VTec X videoscope from KARL STORZ NDTec has been designed to meet the specific demands of rugged industrial use.

Razor-sharp images, easy handling, mobility and an unbeatable price-equipment ratio make the VTec X an all-rounder for multiple inspections.

#### Know-how that provides safety

KARL STORZ NDTec combines the expertise of two leading companies: KARL STORZ, a global leader in the field of medical endoscopy and NDTec, an experienced specialist in non-destructive testing. First-class technology that has proven its worth in the medical field is used for the industrial sector and further developed in an innovative way.

#### Service you can rely on

We possess sound expert knowledge in many areas of application and know what users in many different branches of industry really need. KARL STORZ NDTec offers a customized range of products that includes comprehensive services such as leasing equipment, rapid repair service and favorable contract conditions.



HANDS-FREE: PRACTICAL BACKPACK

For unrestricted freedom of movement. Ideal for applications where a case cannot be transported.



#### COMPATIBLE BATTERY PACK

Suitable for standard batteries.

# SHOCKPROOF HOUSING FOR ROBUST INDUSTRIAL USE

Made of wear- and chemicalresistant synthetic material with shock-absorbing buffers.

## ROBUST PROBE WITH 4-WAY ARTICULATION

Robust – for challenging inspection areas. With stainless steel probe head and tungsten braiding.

360°

#### RAZOR-SHARP DETAILS

High-resolution CMOS sensor in HD quality.



High-power LED light source and high-performance fiber optic light guide.

### VTec X Videoscope

#### **TECHNICAL DATA**

Camera sensor CMOS

LED white light, infrared, ultraviolet

**Screen** 5,5" 16:9, Full HD

**Power supply** 4 rechargeable batteries, type: 18650-protected 3.6/3.7 V

White balance Automatic/manual

Image storage

Photo .bmp Video .avi

Medium SD card, SDHC class 2, max. 128 GB Data transmission SD card, USB 2.0, wireless (optional)

**Articulation** 

Range 360°

Control 4-way motorized with joystick Sensitivity lock, incremental, normal

**Connections** 

Voltage 3.6 V, DC
Data transmission Micro USB 2.0
Image transmission HDMI 2.1

**Base Unit** 

Protection class Handset IP54, probe IP65

Ambient temperature Handset -10°C to +50°C, probe -20°C to +70°C

#### PROBE VERSIONS

Available in diameters of 2.8 / 3.9 / 6.1 mm with standard lengths from 1 - 3 m (max. 8 m) and DOV (Direction of View) of  $0^{\circ}$  and  $90^{\circ}$ ; various DOF (Depth of Field) and FOV (Field of View) options. Probe Data Overview available on karlstorzndtec.com or contact your sales representative.

#### **INCLUDED ACCESSORIES**

- Transportation case
- Battery charger (with 4 slots)
- Li-ion rechargeable batteries 18650-protected, 4 pieces
- Power adaptor

#### OPTIONAL ACCESSORIES

- Backpack
- GTR (Guide Tube Rigid) with handle
- Dekabon tubing (semiflexible guide tube)
- Centering aid (for centering video probes in tubes)
- "Magic Arm" (large or small holder)
- Magnetic stand
- Wireless SD card (WLAN), SD USB reader
- Li-ion rechargeable batteries 18650-protected

Subject to technical changes.

Tel.: +49 (0)9549 9895 44-0

Fax: +49 (0)9549 9895 44-9

E-Mail: info@ksndtec.com