

NATIONAL PAINT REMOVER

DESCRIPTION

A fluffy, paste like stripping compound, to soften, dissolve and remove dry old paint layers.

TYPICAL PROPERTIES

Appearance	Fluffy thick jelly liquid / Hazy
Softening time	15-20 minutes

RECOMMENDED USES

- Over precoated metal, concrete and glass surface.

PACKAGING SIZE

- 0.90 liters
- 3.6 liters
- 18 liters

ADVANTAGES

- Highly effective
- Ready to use
- Removes old emulsion, alkyd, polyurethane and epoxy coatings along with all general purpose coating materials.

CERTIFICATIONS

- Certificates are available upon request

SURFACE PREPARATION

Before application, check the nature of surface. Application can be done by the recommended methods.

SAFETY PRECAUTIONS

- Avoid skin and eye contact by wearing overalls, gloves, goggles, and mask etc.
- Eyes: In the event of accidental splashes, flush eye with water immediately and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water or approved industrial cleaner.
- Avoid inhalation of vapours and paint mist by wearing suitable mask. In the event of ingestion seek medical attention immediately.
- This product is flammable, keep away from sources of ignition. Take precautionary measures against static discharge. In the case of fire, use blanket flames with foam, carbon dioxide or dry chemicals.
- Application must be carried out in well-ventilated area. Local safety regulations need to be followed

APPLICATION METHOD

Dilution	Ready for use
Application method	Brush, Roller, Scraper
Cleaning Thinner	National GP Thinner

METHOD OF USE

- Apply thick coat of National Paint Remover on the required coating surface to be removed.
- Allow to soak the film for 15 – 20 minutes, during this time paint film will start to delaminate from the substrate.
- The delaminated, soaked film along with excess chemical, if any, can be removed with scraper.
- If the film is more thick and hard, it may be necessary to repeat the process more than once.
- After complete removal of paint, clean the surface properly to remove completely any traces of chemicals remains on the surface using water.

STORAGE & SHELF LIFE

- Store the paint in proper storage conditions as per the local regulations. Keep the paint container in sealed condition under shed, away from direct sunlight and extreme temperatures.
- Do not keep paint material near to any ignition sources.
- Do not put back the half or unused material back in original container, containing the supplied paint, to avoid contamination.
- Handle with care.
- Stir well before use.
- Shelf life at 30°C is 18 months in original sealed container, with proper storage conditions.

NOTE: We warranty only the quality of our product and this data sheet is based on results obtained from experience and tests. We reserve the right to change data without prior notice. For safety details kindly refer safety data sheet.