


## GD-CI-DC4617T

4 MP Mini Bullet IP-Camera 4mm ICR IR LED WDR H.265+



- Support Dual Power PoE/DC12V
- 3 Axis Gimbal for wall and ceiling mount
- 0 Lux: Integrated LED IR Illuminator viewable distance up to 30m
- H.265/H.265+, H.264/H.264+ & MJPEG compression modes
- WDR (Wide Dynamic Range) for extreme backlight situations

### ESSENTIAL

- Product Line Essential: high quality, basic features and remarkably many functions for smaller applications

Item Code: GD-CI-DC4617T

EAN CODE: 4260573062140

## Specifications GD-CI-DC4617T

### Camera

Image Sensor:	1/3" progressive Scan CMOS
Video Resolution:	2560 x 1440
Sensitivity Colour:	0.01 Lux @ F1.2 (AGC ON)
Sensitivity B/W:	0 Lux LED IR on
Shutter Speed:	1/3 ~ 1/100,000 s (Automated Electronic Shutter)
Slow Shutter:	Support

### Lens

Lens Focal Length:	4 mm
Horizontal Viewing Angle:	77°
Iris F-Number:	F2.0
Lens Mount:	M12

### Illuminator

Max. IR Distance:	Up to 30 m
Wavelength:	850nm

### Video

Col/B&W:	On, Off, Auto, IR-cut filter removable (ICR)
Wide Dynamic Range:	120 dB
Image Enhancement:	BLC, 3D DNR
Image Settings:	Saturation, brightness, contrast and sharpness adjustable through client software or web browser
Day/Night Switch:	Support auto, scheduled

### Network

Functions:	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, Ip-address filter
Video Compression:	Main Stream: H.264, H.264+, H.265, H.265+ Sub-Stream: H.264, H.265, MJPEG
Region of Interest:	Support 1 fixed region
H.264 code profile:	Baseline Profile / Main Profile / High Profile
Bit Rate:	32Kbps ~ 8Mbps
Network memory:	NAS(NFS, SMB/CIFS)
Network Protocol:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
Cyber Security:	3 levels of user management: admin, operator, user, AES Encryption for Password Protection, Complicated Password, HTTPS (SSL) Login Authentication, Basic and digest authentication for HTTP/HTTPS, 802.1X authentication, (EAP-LEAP), 802.1X authentication (EAP-TLS), 802.1X authentication (EAP-MD5), Watermark, IP Address Filter, WSSE and digest authentication for ONVIF, SNMP V2, SNMP V3, TLS 1.0, TLS 1.1, Brute Force Delay Protection, Secure Boot by software check

Item Code: GD-CI-DC4617T

EAN CODE: 4260573062140

**Network**

Frame Rate:	Main Stream 50Hz: 20 fps @ (2560× 1440) , 25fps @ (2304 × 1296, 1920 × 1080, 1280 × 720) 60Hz: 20 fps @ (2560 × 1440) , 30fps @ (2304 × 1296, 1920 × 1080, 1280 × 720) Sub- Stream 50Hz: 25fps @ (640 x 480, 640 × 360, 320 × 240) 60Hz: 30fps @ (640 x 480, 640 × 360, 320 × 240)
-------------	--

**I/O Interface**

Network Interface:	1x 10, 100 Base T, TX PoE (RJ-45)
--------------------	-----------------------------------

**Intelligent Functions**

Intrusion Detection:	Motion detection,
Event Source:	Video tampering, network disconnected, IP address conflicted

**Approvals**

Regulation:	CE, EAC, FCC, RoHS Compliant
Protection Rating:	IP67
Standard:	ONVIF (Profile S, Profile G), ISAPI

**Environmental**

Operating Temperature:	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Humidity:	Less than 95%, non condensing

**Electrical**

Supply Voltage:	12 VDC, PoE (IEEE 802.3af)
Power Consumption:	Max. 5 W

**Mechanical**

Mount:	Pan: 0° to 360°, tilt: 0° to 180°, rotation: 0° to 360°, 3-Axis Adjustment
Dimensions:	172 × 70 × 65 mm ( 6.77 × 2.75 × 2.56 inch)
Weight:	280 g (0.62 lb)


**Accessories:**

GD-BR-AJX05

**Dimensions:**

Item Code: GD-CI-DC4617T

EAN CODE: 4260573062140



Item Code: GD-CI-DC4617T

EAN CODE: 4260573062140

® Abetechs GmbH (Grundig Security), Düsseldorf, Germany

[grundig-security.com](http://grundig-security.com)