



## Safety Data Sheet (SDS)

No. 5035 Hilco Lube

SDS Revision Date:

05/08/2015

### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product Identity** No. 5035 Hilco Lube  
**Alternate Names** No. 5035

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** Lubricant  
**Application Method** See Label Instructions.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name** Hill Manufacturing Co., Inc.  
1500 Jonesboro Road SE  
Atlanta, GA 30315

#### Emergency

**24 hour Emergency Telephone No.** (800) 535-5053  
**Customer Service: Hill Manufacturing Co., Inc.** (404) 522-8364

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Press. Gas;H280 Contains gas under pressure; may explode if heated.  
Acute Tox. 5;H313 May be harmful in contact with skin. (Not adopted by US OSHA)  
STOT RE 1;H372 Causes damage to organs through prolonged or repeated exposure. Specific Target Organs: (central nervous system )

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger**

H280 Contains gas under pressure; may explode if heated.

H313 May be harmful in contact with skin.

H372 Causes damage to organs through prolonged or repeated exposure.

This product is non-flammable according to ASTM Flame Extension Test.

#### **[Prevention]:**

P260 Do not breathe mist / vapors / spray.  
P262 Do not get in eyes, on skin, or on clothing.  
P264 Wash thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.

#### **[Response]:**

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.  
P312 Call a POISON CENTER or doctor / physician if you feel unwell.  
P314 Get Medical advice / attention if you feel unwell.  
P331 Do NOT induce vomiting.

#### **[Storage]:**

P410+403 Protect from sunlight. Store in a well ventilated place.

**[Disposal]:**

P501 Dispose of contents / container in accordance with local / national regulations.

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
<b>Stoddard solvent</b> CAS Number: 0008052-41-3	25 - 50	STOT RE 1;H372 Asp. Tox. 1;H304	[1][2]
<b>Petroleum distillates, hydrotreated heavy naphthenic</b> CAS Number: 0064742-52-5	25 - 50	Acute Tox. 4;H312	[1]
<b>Distillates (petroleum), hydrotreated middleGasoil - unspecified</b> CAS Number: 0064742-46-7	10 - 25	Asp. Tox. 1;H304 Acute Tox. 4;H332 Skin Irrit. 2;H315	[1]
<b>Carbon dioxide</b> CAS Number: 0000124-38-9	1.0 - 10	Press. Gas;H280 Simple Asphyxiant	[1][2]
<b>Non-Hazardous Ingredient</b> CAS Number: Mixture	1.0 - 10	Not Classified	

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
<b>Ingestion</b>	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Overview</b>	Contact with eyes, prolonged contact with skin may cause irritation. Inhalation - excessive exposure may irritate eyes, nose, and throat. Harmful if swallowed. OTHER HAZARDS: Material may mist when heated. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.
<b>Skin</b>	May be harmful in contact with skin. (Not adopted by US OSHA)

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Do not use; water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of carbon and sulfur

Do not breathe mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

**5.3. Advice for fire-fighters**

Treat as an oil fire. Use a full-faced self-contained breathing apparatus along with full protective gear. Keep nearby containers and equipment cool with a water stream.

**ERG Guide No.** ----

**6. Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).

**6.2. Environmental precautions**

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

**6.3. Methods and material for containment and cleaning up**

Container Warnings: Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAMES, SPARKS, STATIC ELECTRICITY OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE OR CAUSE INJURY OR DEATH. Do not attempt to clean since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. For work on tanks refer to Occupational Safety and Health Administration Regulations, ANSI Z49.1 and other governmental and industrial references pertaining to cleaning, repairing, welding or other contemplated operations.

**7. Handling and storage**

**7.1. Precautions for safe handling**

The requirements of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations apply if the flashpoint is between 21°C and 32°C.

See section 2 for further details. - [Prevention]:

**7.2. Conditions for safe storage, including any incompatibilities**

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

Incompatible materials: Strong Oxidizing Agents, Strong Acids and Alkalis.

See section 2 for further details. - [Storage]:

**7.3. Specific end use(s)**

No data available.

**8. Exposure controls and personal protection**

**8.1. Control parameters**

CAS No.	Ingredient	Exposure	
		Source	Value
0000124-38-9	Carbon dioxide	OSHA	TWA 5000 ppm (9000 mg/m3)
		ACGIH	TWA: 5000 ppm Ceiling: 15000 ppm
		NIOSH	TWA 5000 ppm (9000 mg/m3) ST 30,000 ppm (54,000 mg/m3)
		Supplier	No Established Limit
0008052-41-3	Stoddard solvent	OSHA	TWA 500 ppm (2900 mg/m3)
		ACGIH	TWA: 290 mg/m3 STEL: 580 mg/m3
		NIOSH	TWA 350 mg/m3 C 1800 mg/m3 [15-minute]
		Supplier	No Established Limit
0064742-46-7	Distillates (petroleum), hydrotreated middleGasoil - unspecified	OSHA	No Established Limit
		ACGIH	No Established Limit

		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

#### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000124-38-9	Carbon dioxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0008052-41-3	Stoddard solvent	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-46-7	Distillates (petroleum), hydrotreated middleGasoil - unspecified	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

## 8.2. Exposure controls

### Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

### Eyes

Protective safety glasses recommended.

### Skin

Wear overalls to keep skin contact to a minimum.

### Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

### Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

## 9. Physical and chemical properties

<b>Appearance</b>	Amber Aerosol
<b>Odor</b>	Petroleum Odor
<b>Odor threshold</b>	Not Measured
<b>pH</b>	n/a
<b>Melting point / freezing point</b>	Not Measured
<b>Initial boiling point and boiling range</b>	300 deg F
<b>Flash Point</b>	105 deg F TCC
<b>Evaporation rate (Ether = 1)</b>	Slower than ether
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> Not Measured <b>Upper Explosive Limit:</b> Not Measured
<b>Vapor pressure (mmHg)</b>	5.4 at 70 deg F
<b>Vapor Density</b>	4.5
<b>Specific Gravity</b>	0.8-0.9
<b>Solubility in Water</b>	Nil

<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not Measured
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Not Measured

## 9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

## 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Excessive heat and open flame.

### 10.5. Incompatible materials

Strong Oxidizing Agents, Strong Acids and Alkalis.

### 10.6. Hazardous decomposition products

Oxides of carbon and sulfur

## 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Stoddard solvent - (8052-41-3)	No data available	No data available	No data available	No data available	No data available
Petroleum distillates, hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available
Distillates (petroleum), hydrotreated middleGasoil - unspecified - (64742-46-7)	5,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available
Carbon dioxide - (124-38-9)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	5	May be harmful in contact with skin. (Not adopted by US OSHA)
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable

Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	1	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

## 12. Ecological information

### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available
Petroleum distillates, hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Distillates (petroleum), hydrotreated middle Gasoil - unspecified - (64742-46-7)	54.00, Jordanella floridae	68.00, Daphnia magna	Not Available
Carbon dioxide - (124-38-9)	Not Available	Not Available	Not Available

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	n/a	n/a
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label: ---	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user			

No further information

## 15. Regulatory information

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
<b>Toxic Substance Control Act (TSCA)</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.
<b>WHMIS Classification</b>	A D2A
<b>US EPA Tier II Hazards</b>	<b>Fire:</b> No <b>Sudden Release of Pressure:</b> Yes <b>Reactive:</b> No <b>Immediate (Acute):</b> Yes <b>Delayed (Chronic):</b> Yes

### **EPCRA 311/312 Chemicals and RQs:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **EPCRA 313 Toxic Chemicals:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **N.J. RTK Substances (>1%):**

Carbon dioxide  
Stoddard solvent

### **Penn RTK Substances (>1%):**

Carbon dioxide  
Stoddard solvent

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

**This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

End of Document