

MATERIAL SAFETY DATA SHEET

A Newell Rubbermaid Company

MSDS # 63701

Identification

Sanford, L.P. 2707 Butterfield Road Oak Brook, IL 60523 USA 800-323-0749 or 630-481-2000 EMERGENCY MEDICAL NUMBER:

888-786-0972

Product Name:

Colors:

Section One:

Uni-Paint Px-21 Fine and Px-20 Medium Marker

Black, Red, Blue, Green, Yellow, Violet, Orange, Light Blue, Pink, White, Silver, Gold

Writing Instrument Manufacturers Association (WIMA) certified. Conforms to ASTM D-4236. These markers and the inks contained within have been examined by the WIMA Board Certified Toxicologist in a program of toxicological evaluation to assure they are in compliance with Federal Hazardous Substances Act (FHSA), Labeling of Hazardous Art Materials Act (LHAMA), and ASTM D-4236.

Section Two: Hazard Identification

Acute hazard: At high concentration, dizziness, drowsiness, and unconsciousness may occur. CAUTION: Contains xylene. Harmful or fatal if swallowed. KEEP OUT OF REACH OF CHILDREN. Direct contact may cause skin or eye irritation. **WARNING: This product contains a chemical known to the State of California to cause cancer.

Section Three: Composition

Xylene (1330-20-7), titanium dioxide (13463-67-7), resin, dyes

Section Four:	First Aid Measures
Inhalation:	Move person to fresh air and supply artificial respiration, if necessary.
Skin Contact:	Wash with soap and water.
Eye Contact:	Flush with water. If irritation persists, consult a physician.
Ingestion:	If swallowed, do not induce vomiting. Call a physician.

Section Five:	Fire Fighting Measures	
Flash Point:	34.4C (CC)	
Flammability Limits (% by vol	ume): Lower: 1.1%	Upper: 6.4%
Extinguishing Media:	Dry chemical, carbon dioxide, regu	ılar foam
Special Fire Fighting Measure	s: For large fires, use foam or flood w	vith fine water spray.

Unusual Fire and Explosion Hazards: Avoid inhalation of material or combustion by-products. Stay upwind.

Section Six: Accidental Release Measures

In Case of Spill or Accidental Release: Treat as flammable solvent. Use adequate ventilation.

Section Seven:	Handling and Storage	
Handling:	No special handling requirements.	
Storage:	Keep away from open flames. KEEP OUT OF REACH OF CHILDREN.	
Section Eight:	Exposure Controls and Personal Protection	

Eye Protection:	None under normal use conditions.
Clothing:	None under normal use conditions.
Respirator:	None under normal use conditions.
Ventilation:	Use in a well ventilated area.



MATERIAL SAFETY DATA SHEET

MSDS # 63701

Section Nine:	Physical and Chemical Properties
	For ink unless otherwise specified:
Boiling Point:	138.5C (xylene)
Specific Gravity:	1.25 - 1.32
Vapor Pressure:	6.72 mm Hg at 21C (xylene)
Solubility in Water:	Insoluble
Evaporation Rate:	Not available
Appearance/Odor:	Colored ink; xylene odor
Section Ten:	Stability and Reactivity
Stability:	Stable
Conditions to Avoid:	Avoid heat, flames, sparks, and other sources of ignition.
Chemical Incompatibility:	Strong oxidizers
Hazardous Decompositio	n: Oxides of carbon in fire situation.
Hazardous Polymerizatio	n: Will not occur.

Section Eleven: Toxicological Information

See Section Two: Hazard Identification for any hazards

Section Twelve:	Ecological Information	
Not available		
Section Thirteen:	Disposal Considerations	
Section Thirteen:	Disposal Considerations	

Dispose in accordance v	with Federal,	State,	and Local	Regulations.

Section Fourteen:	Transport Information
DOT:	ORM-D Consumer Commodity
IATA:	Consumer Commodity, 9, ID8000, packing instruction 910
IMO:	Flammable Liquid, n.o.s. (xylene), 3, UN1993, PGIII, (34.4C CC), Ltd. Qtys, EmS# 3-07
Section Fifteen:	Regulatory Information
TSCA:	The product listed on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory.

The product listed on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory. All ingredients used to manufacture this product are listed on the TSCA Inventory

Section Sixteen: Other Information

HMIS Code		
Health	2	
Flammability	3	
Reactivity	0	
Personal Protection	N/A	

Sanford has been advised by Counsel that the OSHA Hazard Communication Standard does not apply to the Sanford Product described in this Material Safety Data Sheet. The reason for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2006 per the Code of Federal Regulations. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by the Hazard Communication Standard nor is this MSDS meant to comply with all requirements of the Hazard Communication Standard.

0=Minimal / 4 = Severe