

TRANSPARENT N/C INKS
BASED ON N/C CHIPS.



CODE	GF 27 -101 (Black) GF 27 -203 (Cyan) GF 27 -602 (Magenta) GF 27 -801 (Yellow)
TYPE	Transparent N/C Inks Based On N/C Chips.
USES	For Different Types Of Paper ,OPP P/P Film ,Polyester Film,Metallized Film And Low&High Density P/E Film.
Properties	• Excellent Adhesion • High Gloss • High Color Strength • Good Heat Resistance
Delivery Viscosity	40 –50 SEC .F.C.NO.4 AT 25 °C For Colours .
Printing Viscosity	16 –20 SEC F.C.NO.4 AT 25 °C For Roto 20-25 SEC F.C.NO.4 AT 25 °C For Flexo
Thinner & Washing	AF 2220/1
Retarder	AF 6095 – AF 6096
Varnish	GF 2223/2-GF22040 And GF22045 (Added To Reduce The Color Strength)
Primer	ULV 300-GF 22-088 Print As Under Lacquer On Metalize Film To Give Good Adhesion. Shelf Life Of ULV 300-GF 22 088 Is Three Months At 25-30° C .
Catalyst	GF 2000/1 Is Added With Ratio (2-5%) To The Ink Before Printing.
Shelf Life Of The Ink	12 Months At 25 –30°C Stirr Well Before Use



PACHIN : FLEXO INK DATASHEET