

# Product datasheet

Specifications



## Easy9 - SPN DB - double door - IP43 - 6 ways

EZ9ESND06

### Main

Range	Easy9
Product name	SPN
Device application	Low voltage electrical distribution
Product or component type	Empty consumer unit
Enclosure type	Metal enclosure
Provided equipment	removable gland plates removable centre plates blanking plate earthing bar comb busbar neutral bar earthing wire DIN rail

### Complementary

Enclosure mounting	Surface Flush
Total number of 18 mm modules	6
Number of horizontal rows	1
Number of ways	6 ways
Protection device type	Miniature circuit breaker (MCB) 1P 63 A 10 kA outgoer Isolator 2P main incomer Miniature circuit breaker (MCB) 2P main incomer Residual current circuit breaker (RCCB) 2P main incomer
Type of front cover	Double door Reversible
[In] rated current	63 A (maximum)
[Ue] rated operational voltage	240 V
Network frequency	50 Hz
Type of rail	DIN
Cable entry	2 knock-outs at left side 2 knock-outs at right side 3 knock-outs at top 3 knock-outs at bottom
Cable cross section	1...25 mm <sup>2</sup>
Comb busbar and distribution block compatibility	YES
Net weight	2.7 kg

<b>Height</b>	224 mm external:
<b>Width</b>	257 mm external:
<b>Depth</b>	93 mm external:
<b>Colour</b>	White (RAL 9003)
<b>Product compatibility</b>	Easy9 RCCB Easy9 switch Easy9 MCB

## Environment

<b>Standards</b>	IEC 61439
<b>IP degree of protection</b>	IP43 conforming to IEC 60529
<b>IK degree of protection</b>	IK08 conforming to IEC 62262

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	2.9 kg
<b>Package 1 Height</b>	9.9 cm
<b>Package 1 width</b>	25.7 cm
<b>Package 1 Length</b>	24.4 cm

## Offer Sustainability

<b>EU RoHS Directive</b>	Under investigation
--------------------------	---------------------