

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION:

- Keep out of reach of children and away from food, drink and animal feed.
- Avoid contact with skin. Wear suitable gloves. May cause sensitization by skin contact.
- Use in well ventilated areas. Do not breathe vapour or spray.
- Do not pour left over paint down the drains or in water courses.
- Contain spillage using sand or earth.
- Store container in an upright position, with lid tightly dosed, in a cool and dry place.
- Safety Data Sheet available for professional user on request.
- No added Lead. Mercury or Chromium compounds.

PRECAUTIONS:

- Avoid extreme temperature.
- Do not apply on damp surface.
- Do not over thin.
- Use only Duwel colorants.
- Stir well before use.
- Tinted paints need thorough shaking immediately after addition as well as before use.
- Wear eye protection while applying.
- Avoid inhalation of dust by wearing a suitable nose pad during sanding or surface preparation.
- In case of contact with eyes, rinse immediately with plenty of water & seek medical advice.
- In case of contact with skin, remove splashes from skin with soap & water or a recognised skin cleaner.
- In case of ingestion seek medical attention.

CONTACT US:

Registered office,
Akzo Nobel India Limited Geetanjali Apartment, 1st floor, 8B Middleton Street, Kolkata 700 071
In case of any complaints please contact Customer care cell,
Akzo Nobel India Ltd., 9th Floor, Magnum Towers, Golf Course Ext Rd, Sector 58, Gurugram, 122011,
Haryana, India

Note: The information provided above may change without prior notice.



VelvetTouch

PEARL GLO

PRODUCT DATA SHEET



PRODUCT DESCRIPTION :

Dulux Velvet Touch Pearl Glo is a premium quality, highly durable and washable emulsion paint with a best in class mid sheen luxury finish. It is the only super premium interior emulsion that brings alive the smooth touch of velvet and soft glo of pearls on the walls.



PRODUCT FEATURES AND BENEFITS :



Equipped with a unique and specialised Core & Shell Technology, Dulux Velvet Touch Pearl Glo is the only Super Premium Interior Emulsion that brings alive the smooth touch of Velvet & long lasting Pearl Glo Finish on your walls. Being the only luxury emulsion to be enriched with essence of PEARLS, Velvet Touch gives walls a unique and long lasting Pearl Glow Finish – a perfect reflection of 'Elegance' & 'Class' on walls.



Velvet Touch Pearl Glo has been specially formulated to provide a long lasting colour and finish durability with best in class scrub resistance, opacity and washability.



Best-in-Class Smoothness - with a 'Touch of Velvet' and enhanced flow-ability makes the application extremely easy & smooth.

PRODUCT RELATED INFORMATION :

Film Composition:

Pigment	: Non-lead pigment
Binder	: Acrylic copolymer emulsion
Solvent	: Water
Gloss/ Sheen Level	: Mid Sheen pearl glow finish
Flash Point (IS 101/1987, Part 1, sec 6)	: Non-Flash
Stability of Thinned Paint	: Can be used within 24 hours of thinning after mixing
Dry Film Thickness (Calculated)	: 20-25 microns at a coverage of 160-180 sq ft/ litre
Coverage	: The Spreading capacity/coverage of this product will vary considerably according to the surface preparation, roughness and porosity of the surface and change in color on the wall <ul style="list-style-type: none">• On smooth surface of low porosity: Range 140-160 sqft/litre/2 coats• On high porous absorbent surface: Range 120-140 sqft/litre/2 coats
Pack Size Available	: 1, 4, 10 & 20 litres

APPLICATION RELATED INFORMATION:



Application Tool :

Suitable for application by brush roller and spray.



Surface Preparation :

- New concrete/ plaster surface should allowed to mature property.
- Ensure that the surface is clean, dry, free from all loose particles, dust, dirt, grease, wax, mould, fungal growth etc. before application.
- All surfaces should be thoroughly rubbed down using a suitable abrasive paper and thereafter wiped off.
- Suitable remedial measures should be taken in case of water seepage/ leakage problems
- Fungus affected areas need separate treatment.
- Proper surface preparation is a must to get the desired effect & finish.



Priming:

- Prime surface with a coat of ICI Cement primer (34-200) or ICI water based cement primer (320168) and dry overnight.
- Use a mixture of 1 part of Dulux Velvet Touch with 1 part of whiting or oil based putty or ICI readymade wall filter (33-500) to rectify and smootnensout the surface. Allow drying for 4-6 hours.
- Sand the surface with Emery Paper 180. Wipes off loose particles. Apply another coat of primer. Allow drying for 4-6 hours. Sand the surface with Emery Paper 380 and wipe clean.
- Primer putty is a must to get the desired effect.



Dilution:

- 40% {20-25% : Dark Shades}. Do not over dilute and shake the paint well before use.



Finishing:

- Stir thoroughly before use.
- Apply 2 coats of Dutux Velvet Touch Emulsion with minimum 4 hours between the coats. Normally two coats of part are sufficient for opacity and the desired finish. However on extracoat may be requirement for change of colour.



Drying Time:

- Touch Dry : 30 Minutes
- Recoat : 4 hours.
- Drying time may vary according to the temperature and humidity.

POST APPLICATION INSTRUCTIONS :

For best performance of the paint, ensure proper washing and cleaning at regular intervals of six months.