

AkzoNobel

SAFETY DATA SHEET

A1510250 0463510-B-1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Dulux Weathershield MAX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : This product is for test purposes only.

1.3. Details of the supplier of the safety data sheet

AkzoNobel India Limited

ICI Research & Technology Centre Plot No. 1/1, TTC Industrial Area, Thane Belapur Road, Koparkhairne,

Navi Mumbai, Maharashtra, INDIA. 400 710.

www.akzonobel.com

email address : santan.hajra@akzonobel.com

1.4 Emergency telephone number

Telephone number : 02227789544

Version : 1

Date of previous issue : No previous validation

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown : 0%

toxicity

Ingredients of unknown

: 0%

ecotoxicity

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Date of issue/Date of revision : 1/19/2022 Page: 1/16

SECTION 2: Hazards identification

Hazard pictograms





Signal word : Warning

Hazard statements H317 - May cause an allergic skin reaction.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

General : P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention : P280 - Wear protective gloves.

P273 - Avoid release to the environment.

P261 - Avoid breathing vapour.

: P391 - Collect spillage. Response

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national or international regulations.

Hazardous ingredients 1,2-benzisothiazol-3(2H)-one

2-methyl-2H-isothiazol-3-one

C(M)IT/MIT(3:1)

: Not applicable.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

Annex XVII - Restrictions on the manufacture,

placing on the market and use of certain dangerous substances, mixtures and

articles

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No.

1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
ethanediol	EC: 203-473-3 CAS: 107-21-1 Index: 603-027-00-1	≤3	Acute Tox. 4, H302	[1] [2]
diuron (ISO)	EC: 206-354-4 CAS: 330-54-1 Index: 006-015-00-9	<1	Acute Tox. 4, H302 Carc. 2, H351 STOT RE 2, H373 Aquatic Acute 1, H400	[1]

Date of issue/Date of revision : 1/19/2022 Page: 2/16

· · · · · · · · · · · · · · · · · · ·		_	(M=10)	
			Aquatic Chronic 1, H410 (M=10)	
phosphorus pentoxide	EC: 215-236-1 CAS: 1314-56-3 Index: 015-010-00-0	<1	Skin Corr. 1Á, H314	[1] [2
pyrithione zinc	EC: 236-671-3 CAS: 13463-41-7	<0.3	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360 STOT RE 1, H372 Aquatic Acute 1, H400 (M=1000) Aquatic Chronic 1, H410 (M=10)	[1]
ammonia	EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	≤0.3	Skin Corr. 1B, H314 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	[1]
methylisothiazolinone	EC: 220-239-6 CAS: 2682-20-4 Index: self classification	<0.1	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1) EUH071	[1]
			See Section 16 for the full text of the H statements declared	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

above.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid m	asures
General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Date of issue/Date of revision : 1/19/2022 Page: 3/16

SECTION 4: First aid measures

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, C(M)IT/MIT(3:1). May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters

: Appropriate breathing apparatus may be required.

Date of issue/Date of revision : 1/19/2022 Page: 4/16

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking, Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds

Danger criteria

Date of issue/Date of revision : 1/19/2022 Page: 5/16

SECTION 7: Handling and storage

	Notification and MAPP threshold	Safety report threshold
E1	100 tonne	200 tonne

7.3 Specific end use(s)

solutions

Recommendations : Not available.

Industrial sector specific : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
ethanediol	EU OEL (Europe, 2/2017). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 20 ppm 8 hours. TWA: 52 mg/m³ 8 hours. STEL: 40 ppm 15 minutes.
phosphorus pentoxide	STEL: 104 mg/m³ 15 minutes. EU OEL (Europe, 2/2017). Notes: list of indicative occupational exposure limit values TWA: 1 mg/m³ 8 hours.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
pyrithione zinc	DNEL	Long term Dermal	0.01 mg/ kg bw/day	Workers	Systemic

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Date of issue/Date of revision : 1/19/2022 Page: 6/16

SECTION 8: Exposure controls/personal protection

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

: Use safety eyewear designed to protect against splash of liquids.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm.

When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended.

Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Body protection

: Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

OLD LEAD-BASED PAINTS:

When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead-pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.

Where possible wet sanding or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry sanding cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

Respiratory protection in case of dust or spray mist formation. (particle filter EN143 type P2) Respiratory protection in case of vapour formation. (half mask with combination filter A2-P2 til concentrations of 0,5 Vol%.)

The current Control of Lead at Work Regulations approved code of practice should be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations. All scrapings, dust, etc. should be disposed of by the professional painting contractor as Hazardous Waste.

Extra precautions will also need to be taken when burning off old lead-based paints because fumes containing lead will be produced. It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Similar precautions to those given above about sanding should be taken with reference to protective clothing, disposal of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.

Date of issue/Date of revision : 1/19/2022 Page: 7/16

SECTION 8: Exposure controls/personal protection

Avoid the inhalation of dust. Wear suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Environmental exposure

controls

: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Various: See label. : Not available. Odour : Not available. **Odour threshold**

pН 9.5

Melting point/freezing point : Not available.

Initial boiling point and boiling

range

: 100°C

Flash point : Not applicable. **Evaporation rate** : Not available. **Upper/lower flammability or** : Not available.

explosive limits

: Not available. Vapour pressure Vapour density : Not available.

Relative density 1.301

Solubility(ies) : Easily soluble in the following materials: cold water.

Partition coefficient: n-octanol/ : Not available.

water

Auto-ignition temperature : Not available. **Decomposition temperature** : Not available.

: Kinematic (room temperature): 5.38 cm²/s **Viscosity**

Explosive properties : Not available. : Not available. **Oxidising properties**

9.2. Other information

Solubility in water : Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Date of issue/Date of revision : 1/19/2022 Page: 8/16

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, C(M)IT/MIT(3:1). May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanediol	LD50 Intraperitoneal	Rat	5010 mg/kg	-
	LD50 Intravenous	Rat	3260 mg/kg	-
	LD50 Oral	Rat	4700 mg/kg	-
	LD50 Route of exposure	Rat	13 g/kg	-
	unreported			
	LD50 Subcutaneous	Rat	2800 mg/kg	-
phosphorus pentoxide	LC50 Inhalation Vapour	Guinea pig	61 mg/m ³	1 hours
	LC50 Inhalation Vapour	Mouse	271 mg/m ³	1 hours
	LC50 Inhalation Vapour	Rabbit	1689 mg/m ³	1 hours
	LC50 Inhalation Vapour	Rat	1217 mg/m³	1 hours

Conclusion/Summary

: Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
DWS MAX Brilliant White Cogrind (Q01P) 463500 4126771	26315.8	N/A	N/A	N/A	27.8
ethanediol	500	N/A	N/A	N/A	N/A
diuron (ISO)	500	N/A	N/A	N/A	N/A
pyrithione zinc	100	N/A	N/A	N/A	0.05
methylisothiazolinone	100	300	N/A	0.5	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanediol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Mild irritant	Rabbit	-	1 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	6 hours 1440 milligrams	-
	Skin - Mild irritant	Rabbit	-	555 milligrams	-
ammonia	Eyes - Severe irritant	Rabbit	-	250 ug	-
	Eyes - Severe irritant	Rabbit	-	0.5 minutes 1 mg	-

Conclusion/Summary

: Not available.

Sensitisation

Date of issue/Date of revision : 1/19/2022 Page: 9/16

SECTION 11: Toxicological information

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ammonia	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
diuron (ISO) pyrithione zinc	Category 2 Category 1	-	-

Aspiration hazard

Not available.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
ethanediol	Acute LC50 13140000 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 13900000 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 10500000 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6900000 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 10000000 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 41100000 μg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 47400000 μg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 46300000 μg/l Fresh water		48 hours
	Acute LC50 45500000 μg/l Fresh water		48 hours
	Acute LC50 41000000 μg/l Fresh water		48 hours
	Acute LC50 27540 mg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 52500 mg/l Fresh water	Fish - Pimephales promelas -	96 hours

Date of issue/Date of revision : 1/19/2022 Page: 10/16

SECTION 12: Ecological information

	1	T	ı
	Acute LC50 43900 mg/l Fresh water	Fry Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling,	96 hours
	Acute LC50 49000000 μg/l Fresh water	Weanling) Fish - Pimephales promelas -	96 hours
		Juvenile (Fledgling, Hatchling, Weanling)	
diverse (ISO)	Acute LC50 8050000 µg/l Fresh water	Fish - Pimephales promelas	96 hours 96 hours
diuron (ISO)	Acute EC50 0.0023 mg/l Fresh water Acute EC50 2.4 ppb Fresh water	Algae - Chlorella pyrenoidosa Algae - Pseudokirchneriella	96 hours
	Note 2000 2.4 pps 1 real water	subcapitata	Jo Hours
	Acute EC50 0.005 mg/l Fresh water	Aquatic plants - Lemna sp.	96 hours
	Acute EC50 7.6 μg/l Fresh water	Aquatic plants - Lemna aequinoctialis	72 hours
	Acute EC50 8.6 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 8.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 8.4 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute IC50 2.41 μg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Acute IC50 5.89 μg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Acute IC50 2.47 μg/l Marine water Acute LC50 3044 μg/l Marine water	Aquatic plants - Zostera muelleri Crustaceans - Palaemon	72 hours 48 hours
		serratus - Zoea	
	Acute LC50 1.95 ppm Fresh water Acute LC50 3100 µg/l Fresh water	Fish - Oncorhynchus mykiss Fish - Morone saxatilis	96 hours 96 hours
	Acute LC50 2900 µg/l Fresh water	Fish - Cyprinus carpio - Fry	96 hours
	Chronic EC10 0.11 µg/l Fresh water	Algae - Fragilaria capucina - Exponential growth phase	96 hours
	Chronic EC10 0.76 µg/l Fresh water	Algae - Fragilaria capucina ssp. rumpens	96 hours
	Chronic IC10 0.47 µg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Chronic IC10 0.7 μg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Chronic IC10 0.49 µg/l Marine water	Aquatic plants - Zostera muelleri	72 hours
	Chronic NOEC 0.283 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.34 µg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Chronic NOEC 0.34 µg/l Marine water Chronic NOEC 26.4 ppb	Aquatic plants - Zostera muelleri	72 hours 60 days
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas Fish - Pimephales promelas	60 days
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas	60 days
	Chronic NOEC 33.4 µg/l Fresh water	Fish - Pimephales promelas - Embryo	63 days
pyrithione zinc	Acute EC50 0.51 μg/l Marine water	Algae - Thalassiosira pseudonana	96 hours
	Acute EC50 8.25 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2.68 ppb Fresh water	Fish - Pimephales promelas	96 hours
	Chronic EC10 0.36 µg/l Marine water	Algae - Thalassiosira pseudonana	96 hours
	Chronic NOEC 2.7 ppb Fresh water	Daphnia - Daphnia magna	21 days
ammonia	Acute LC50 37 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours
methylisothiazolinone	Acute EC50 0.24 mg/l	Daphnia	48 hours
	Acute EC50 0.18 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.18 mg/l	Fish Lenomic Macrochirus	96 hours 96 hours
	Acute LC50 12.4 mg/l Acute LC50 6 mg/l	Fish - Lepomis Macrochirus Fish - Oncorhynchus Mykiss	96 hours
	Acute LC50 0 mg/l	Fish - Oncorhynchus mykiss	96 hours
Conclusion/Summary	Net available		1

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

Date of issue/Date of revision : 1/19/2022 Page: 11/16

SECTION 12: Ecological information

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ethanediol	-1.36	-	low
diuron (ISO)	2.84	5.2	low
pyrithione zinc	0.9	11	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Disposal considerations

: The classification of the product may meet the criteria for a hazardous waste.

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information, contact your local waste authority.

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging		European waste catalogue (EWC)
CEPE Paint Guidelines	15 01 10*	packaging containing residues of or contaminated by hazardous substances

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 1/19/2022 Page: 12/16

SECTION 14: Transport information

	ADR	IMDG
14.1. UN number	UN3082	UN3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (diuron (ISO))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (diuron (ISO))
14.3. Transport hazard class(es) Class	9	9
Subsidiary class	-	-
14.4. Packing group	III	III
14.5. Environmental hazards		
Marine pollutant	Yes.	Yes.
Marine pollutant substances		diuron (ISO)
14.6. Special precautions for user	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	
HI/Kemler number	90	
Emergency schedules (EmS)		F-A, S-F
14.7 Transport in bulk : Not applicable. according to IMO instruments		
Additional information	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

14.7 Transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed, or the component present is below its threshold.

Substances of very high concern

None of the components are listed, or the component present is below its threshold.

Date of issue/Date of revision : 1/19/2022 Page: 13/16

SECTION 15: Regulatory information

Annex XVII - Restrictions : Not applicable.

on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC for Ready-for-Use : Not applicable.

Mixture

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety : No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Product code : SAMPLE A1510250 0463510-B-1

CEPE code

Indicates information that has changed from previously issued version.

Abbreviations and acronyms: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Acute 1, H400	Calculation method Calculation method Calculation method

Date of issue/Date of revision : 1/19/2022 Page: 14/16

SECTION 16: Other information

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated
	exposure.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

ACUTE TOXICITY - Category 2
ACUTE TOXICITY - Category 3
ACUTE TOXICITY - Category 4
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
CARCINOGENICITY - Category 2
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
REPRODUCTIVE TOXICITY - Category 1B
SKIN CORROSION/IRRITATION - Category 1A
SKIN CORROSION/IRRITATION - Category 1B
SKIN SENSITISATION - Category 1
SKIN SENSITISATION - Category 1A
SPECIFIC TARGET ORGAN TOXICITY - REPEATED
EXPOSURE - Category 1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED
EXPOSURE - Category 2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -
Category 3

Date of printing : 1/19/2022 Date of issue/ Date of : 1/19/2022

revision

Date of previous issue : No previous validation

Version : 1

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Date of issue/Date of revision : 1/19/2022 Page: 15/16

SECTION 16: Other information

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands

Date of issue/Date of revision : 1/19/2022 Page: 16/16