



SAFETY DATA SHEET RENDEROC BF

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RENDEROC BF

Product number 2182000AE1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cementitious overlay

1.3. Details of the supplier of the safety data sheet

Supplier Al Gurg Fosroc LLC
 PO Box 657
 Dubai
 United Arab Emirates
 + 971 4 2858606

1.4. Emergency telephone number

Emergency telephone +97142039699 (08:00 to 16:30) // +971506258232 (16:30 to 08:00)GMT+4

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

Human health

Dust or splashes from the mixture may cause permanent eye damage. Dust may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Dust has an irritating effect on moist skin. Prolonged contact with moist or wet product may cause burns. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

Environmental

The product will harden into a solid mass in contact with water and moisture. The resultant material is not biodegradable.

2.2. Label elements

Hazard pictograms



Signal word

Danger

RENDEROC BF

Hazard statements	H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.
Precautionary statements	P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/ container in accordance with national regulations.
Contains	SILICA SAND, ORDINARY PORTLAND CEMENT

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SILICA SAND	30-60%
CAS number: 14808-60-7	
Classification Eye Irrit. 2 - H319 STOT SE 3 - H335	
ORDINARY PORTLAND CEMENT	30-60%
CAS number: 65997-15-1 EC number: 266-043-4	
Classification Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Dust in throat and nasal passages should clear spontaneously. Get medical attention if irritation persists or later develops, or if discomfort, coughing or other symptoms persist.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Skin contact	After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Do not rub eye. Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

RENDEROC BF

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.
Ingestion	Ingestion of large doses may result in irritation to the gastrointestinal tract.
Skin contact	May have an irritating effect on moist skin after prolonged contact, or may cause dermatitis after repeated contact. Prolonged skin contact with wet preparation may cause serious burns without pain being felt, including through clothing.
Eye contact	Eye contact may cause serious and potentially irreversible injuries.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Water used for fire extinguishing, which has been in contact with the product, may be corrosive. No unusual fire or explosion hazards noted.
-------------------------	--

Hazardous combustion products	No known hazardous decomposition products.
--------------------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
---	---

Special protective equipment for firefighters	Use protective equipment appropriate for surrounding materials.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid inhalation of dust. Use work methods which minimize dust production. Avoid contact with eyes and prolonged skin contact. Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Collect and dispose of spillage as indicated in Section 13. Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Dry material: Collect powder using special dust vacuum cleaner with particle filter. Alternatively, damp powder with fine spray (to avoid dust formation) and remove slurry. Place into container and allow to solidify before disposal as described in section 13. Wet material: Clean up wet material and place in a container. Allow to dry and solidify before disposal as described in section 13.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see section 13.
------------------------------------	---

RENDEROC BF

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Avoid generation and spreading of dust. Avoid inhalation of dust. Mechanical ventilation or local exhaust ventilation may be required. Change contaminated clothing. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place. Unsuitable container materials: Aluminium. Seal opened containers and use up as soon as possible. To be stored out of reach of children in its original packaging in a dry place.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

SILICA SAND

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m³

ORDINARY PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

WEL = Workplace Exposure Limit.

ORDINARY PORTLAND CEMENT (CAS: 65997-15-1)

DNEL

Workers - Inhalation; Short term : 3 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.

Personal protection

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. This product may present a chromate (VI) allergy risk. Users should wear appropriate personal protective equipment.

Eye/face protection

The following protection should be worn: Chemical splash goggles. (conform EN 166)

Hand protection

Use impervious, abrasion and alkali resistant gloves. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

Other skin and body protection

Use barrier creams to minimise skin contact. Wear appropriate clothing to prevent repeated or prolonged skin contact.

RENDEROC BF

Hygiene measures	<p>This product contains silica sands.</p> <p>The grain size distribution of silica sand present means that it is not classified as hazardous. However, any respirable crystalline dust generated by secondary processing may cause health effects.</p> <p>Prolonged and /or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness.</p> <p>Occupational exposure to respirable crystalline silica dust should be monitored and controlled.</p>
Respiratory protection	Wear a respirator fitted with the following cartridge: Particulate filter, type P2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Dusty powder.
Colour	Grey.
Odour	Odourless.
Odour threshold	Not relevant.
pH	pH (concentrated solution): >12
Melting point	>1250°C
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	The product is not flammable.
Other flammability	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	2.05 @ 20°C
Bulk density	Not determined.
Solubility(ies)	Soluble in water.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not applicable.
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.
Comments	Information given is applicable to the product as supplied.

RENDEROC BF

9.2. Other information

Other information No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity When mixed with water, hardens to form a stable mass that is not reactive in normal conditions.

10.2. Chemical stability

Stability Stable under the prescribed storage conditions. This product has a shelf life. If not stored in accordance with packaging instructions (sealed and dry) There is a risk of the presence of hexavalent chromate leading to a risk of an allergic reaction

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not known. Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Water, moisture.

10.5. Incompatible materials

Materials to avoid Acids. Chemically-active metals.

10.6. Hazardous decomposition products

Hazardous decomposition products No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin sensitisation

Skin sensitisation Some individuals may exhibit eczema upon exposure to wet cement caused either by the high pH which induces irritant contact dermatitis, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis.

Inhalation

Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to cement dust.

Ingestion

May cause irritation of mouth, throat and digestive tract.

Skin contact

This product is strongly irritating. Prolonged contact may cause burns. May cause sensitisation by skin contact.

Eye contact

Irritating and may injure eye tissue if not removed promptly.

Acute and chronic health hazards

Repeated and/or prolonged contact may lead to dermatitis.

Toxicological information on ingredients.

ORDINARY PORTLAND CEMENT

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.0 mg/kg)

RENDEROC BF

Species

Rabbit

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

ORDINARY PORTLAND CEMENT

Acute aquatic toxicity

Acute toxicity - fish Not determined.

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product hardens to a solid, immobile substance. The product is not volatile but may be spread by dust-raising handling.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not empty into drains, sewers or water courses.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not relevant.

14.2. UN proper shipping name

Not relevant.

14.3. Transport hazard class(es)

Not relevant.

Transport labels

No transport warning sign required.

14.4. Packing group

Not relevant.

RENDEROC BF

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not relevant.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not relevant.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	23/11/2020
Revision	3
Supersedes date	26/07/2018
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.