

FABUFILL

LITE PRODUCT DATASHEET







DESCRIPTION

Thermally Bonded Polyester Insulation

Platinum Fibre's Fabufill LITE polyester insulation is a versatile, easy to install, flexible, strong, lightweight blanket and is manufactured from recycled PET (polyethylene terephthalate) plastic bottles. Produced in a range of different thickness to provide a myriad of thermal and acoustic performances. This non-allergenic, non-irritant and resilient insulation does not support the spread of flame (Class B/B1/2 fire rating).

Used in roofs, cellings, partitions and walls and is manufactured in widths to suit standard spacings of studs, celling and floor joists.

After its use, Fabufill's LITE polyester insulation can be easily recycled, making this the perfect 'cradle to grave' insulation product.

MATERIAL DATA

Thickness (mm): Minimum 50mm. (Allow up to 30 days for full recovery of loft).

Roll dimensions (I x w): 10.0 (I) x 0.60 OR 0.75 OR 1.2 (w) metres (tolerance +25mm and -10mm).

Fibre composition: 80% recycled PET (locally sourced) & 20% virgin LMF.

APPLICATIONS



roof



ceiling



partition



wall

PERFORMANCE

R-Value: 0.82 m2.K/W (determined in accordance with ASTM C517).

Fire: B/B1/2/H (determined in accordance with SANS 428)

Non-Flammable. Will not contribute to the spreading of flame and will self-extinguish

when a heat source is removed.

Combustibility Data: Combustible at over 750 degrees (determined in accordance with SANS 10177-8).





ENVIRONMENTAL

Ozone depleting substances: Does not contain and did not produce any during production. No VOC's are used during

the production of this material.

Recycling: 1 ton of Fabufill's polyester insulation is manufactured from approximately 38 000

recycled bottles.

The plastic bags used for transporting the material are made from virgin LDPE material and is 100% recyclable, Grade 4. The inks used in the packaging are food grade.

SPECIFICATION CLAUSE

Clause: Fabufill LITE thermally bonded polyester insulation Roll, thermal and acoustic insulation

installed between trusses, joists, studs or above suspended ceilings, non-combustible to

SANS 10177-8 and B/B1/2/H to SANS 428. Compression packed.

HANDLING & STORAGE

Safety Precautions: No particular hazards are known. The polyester fibres are not known to cause allergies.

With correct use of this product no detrimental effects on health have been recorded.

Transportation: The rolls are compressed into plastic bags and is classified as non-hazardous.

Storage: Rolls to be stored under cover, laid horizontally and stacked no more than 10 units high.

Rolls should be kept dry and must not be exposed to a naked flame or any other

ignition source.





INSTALLATION GUIDELINES

Installation tools: Fabufill polyester insulation can be easily torn or cut with a pair of industrial scissors or shears.

Installation methods: Lay loose on ceiling board or suspended between trusses with restraining wires at 300mm intervals.

The distance between roof trusses, ceiling joists and walls studs should be measured, and the

appropriate roll widths used.

Fabufill rolls should be installed between the members and the ends of the rolls should be carefully

butted or lapped to ensure that the insulation is continuous.

A 50mm gap should be created around downlighters, recessed lights, flue pipes or any low heat

sources.

OTHER INFORMATION:

Durability: Fabufill does not physically deteriorate over time and does not require any maintenance.

Properties are such that the material will not be damaged during normal handling and installations.

Fungal Attack: Fabufill has good resistance to bacteria, fungi and mildew and fibre-devouring insects will not

damage Fabufill polyester insulation since it is indigestible (tested in accordance with SANS 5484.)

Moisture Absorption: 0.78% (SANS 1381-1:2013 allows up to 2%)



FABUFILL

LITE PRODUCT DATASHEET

CONTACT:

t: 011 421 0933

m: info@platinumfibre.com

w: www.platinumfibre.com

Platinum Fibre provides all information contained in this publication based on data available at the time and reserves the right to amend such information from time to time.