



MAXAM

MS931

LOGXTRA - LS2 FORESTRY

Designed for use on demanding forestry equipment. High strength, belt stabilized tire construction provides excellent traction and flotation in severe logging applications.

- Heavy duty shoulder and sidewall
- Maximum protection from cuts, impact, and punctures
- Cut resistant compound specifically engineering for forestry service
- Steel reinforced undertread
- Nylon-wrapped beads prevent unwinding

Applications:



Size	PR	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi kPa	20 mph 30 kph	
23.1-26	16	TL	DW20B	63.8	22.8	72	35	9900	160A6
				1620	580	58	240	4500	
28L-26	16	TL	DW25B	63.9	28.0	76	30	10500	162A6
				1624	710	60	210	4750	
	20	TL	DW25B	64.1	27.8	76	35	11400	165A6
				1628	707	60	240	5150	
26	TL	DW25B	64.1	27.8	76	50	14300	173A6	
			1628	707	60	340	6500		
24.5-32	20	TL	DH21	72.1	24.5	75	40	13200	170A6
				1831	622	60	275	6000	
30.5L-32	20	TL	DH27	73.0	30.3	82	30	13200	170A6
				1855	769	65	205	6000	
	26	TL	DH27	73.0	30.2	82	40	15700	176A6
				1855	768	65	275	7100	
32	TL	DH27	73.0	30.2	82	50	17600	180A6	
			1855	768	65	340	8000		
35.5L-32	20	TL	DH31	79.2	35.5	84	25	16100	177A6
				2011	902	67	175	7300	
	26	TL	DH31	79.2	35.5	84	35	19300	183A6
				2011	902	67	240	8750	
	30	TL	DH31	79.2	35.5	84	40	20900	186A6
				2011	902	67	275	9500	

