




Applications



Classrooms



Retail



Home



Large surfaces











Hotels






Restaurants

Specifications (Series luminaires)

	Voltage (V)	220-240V
Hz	Frequency (Hz)	50-60Hz
	Current (A)	1.050mA
ϕ	Power factor (Cos fi)	0.96
	Dimming	No


	IP Tightness index	IP44
	Body color	White
	Diffuser Material	VT
	Body	AL
	Reflector	AL AN

K	Colour temperature	3.000K
---	---------------------------	--------

	Measures	Ø190x140mm
	Mounting position	Empotrar
	Inclination	50°/+135°/-135°


ϕ_{LUM}	Flux (lm)	3.557lm
--------------	------------------	---------

	Electrical isolation	CII
---	-----------------------------	-----





	Lifetime	L70>30.000h
---	-----------------	-------------

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.


Dimensions




References

	W_{LED}	W		ϕ_{LED}	ϕ_{LUM}		K	
144551	35W	38W	1050mA	3.909lm	3.557lm	40°	3.000K	Ø190x140mm

On request



Dali



Emergency kit

Solutions

S



CTE Pack

description

Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.



CLASSROOMS Pack

description

Regulation by contribution of natural light and stand alone presence. Lighting control system to meet CTE requirements and optimize energy use by taking advantage of natural light and automatic shutdown in case of absence.



Bluetooth package

description

Casambi version of our fixtures that enables through any Bluetooth® terminal via free APP that offers the control of flow regulation, color, scene configuration, behavior linked to schedules. Multiple accessories can be configured to work on the same network to unify the control of one or more spaces, being able to create groups, scenes and dynamic sequences to measure. The Bluetooth® device is valid for any DALI luminaire.

Info

For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es

Info



You need DALI drive

Info



Transparent glass with matte central section for an adequate glare control