

Specifications (Series luminaires)							
<u></u>	Electrical isolation	CII					
4	Voltage (V)	180-250V					
Hz	Frecuency (Hz)	50-60Hz					
\bigcirc	Dimming	No					
0 0	IP Tightness index	IP20					
\odot	Body color	White					
11/	Diffuser Material	PC-O					
	Body	AL					
K	Colour temperature	3.000K					
Ø	CRI Colour rendering index	>80					
Д	Opening angle	120°					
\longleftrightarrow	Measures	125x30mm					
←	Mounting position	Empotrado Techo					
fltc	Operating temperature	-5°C~+35 °C					
ф	Flux (lm)	609lm					
	Lifetime	(L70B50>) 50.000h					






References										
	W	ф _{илм}	K	À	(\longleftrightarrow	\bigcirc		
381567	6W	609lm	3.000K	>80	White	100-110	125x30mm	No		

Dimensions

Photometry









On request





Emergency kit 2hBajo el campo de configuración se añade solo este texto, en los 4 idiomas definidos

Accessories





532211

DRIVER KENTAU 6W 1-10V





Technologies Explanation of the second secon



CELLTECH



CELLTECH technology is a revolutionary feeding system for luminaires that allow the extraction and exchange of drivers that facilitates

and simplifies the installation and mounting of luminaires. CELLTECH drivers are available without regulation and with 1-10V regulation and C-TOUCH.





Solutions S



CTE Pack



CLASSROOMS Pack

description



Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.

description



Regulation by contribution of natural light and stand alone presence. Lighting control system to meet CTE requirements and optimize energy use by taking advantage of natural light and automatic shutdown in case of absence.

BLUETOOTH Pack

description



Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es