

















## Specifications (Series luminaires)




|   |                                   |                   |
|---|-----------------------------------|-------------------|
|    | <b>Voltage (V)</b>                | 230V              |
|    | <b>Frecuency (Hz)</b>             | 50-60Hz           |
|    | <b>Power factor (Cos fi)</b>      | >0,7              |
|    | <b>Dimming</b>                    | Yes               |
|    | <b>Bushing type</b>               | E27               |
|    | <b>IP Tightness index</b>         | IP20              |
|    | <b>Colour temperature</b>         | 2.500K            |
|    | <b>CRI Colour rendering index</b> | >80               |
|    | <b>Opening angle</b>              | 280°              |
|  | <b>Measures</b>                   | 125x178mm         |
|  | <b>Operating temperature</b>      | -5°C~+35 °C       |
|  | <b>Flux (lm)</b>                  | 736lm             |
|  | <b>Lifetime</b>                   | (L70B50>) 15.000h |
|  | <b>CEE Energy classification</b>  | F                 |

## References



|  | W    | $\phi$ | $\phi_{LUM}$ | K      | $\leftrightarrow$ |
|---|------|--------|--------------|--------|-------------------|
| <b>402200</b>   | 7,5W | >0,7   | 736lm        | 2.500K | 125x178mm         |

## Dimensions



## Photometry

