



Specifications (Series luminaires)							
	Electrical isolation	CII					
4	Voltage (V)	230V					
Hz	Frecuency (Hz)	50-60Hz					
0	Dimming	No					
L O O O	IP Tightness index	IP20					
000	IP installed Sealing rating	40					
	Body color	White					
1/1	Diffuser Material	РММА-О					
	Body	FE					
K	Colour temperature	3.000K					
Ø	CRI Colour rendering index	≥80					
Д	Opening angle	120°					
$ \Longleftrightarrow $	Measures	600x600x7,5mm					
←	Mounting position	Empotrado Techo					
Atc	Operating temperature	-5 +35					
\$LUM	Flux (lm)	3664lm					
(⁷⁰	Lifetime	L70 >50.000h					







References											
	₩ _{LED}	W		ф	ф	K		\bigcirc			
404693	40W	43W	1000mA	4583lm	3664lm	3.000K	575x575	No			

Dimensions ←

Photometry












On request







Dali

Bluetooth

Accessories









964562

FRAME WH RECESSED PLASTER SILENT LED 60X60CM

164092

WH SURFACE DRAWER SILENT LED 60X60CM

397391

RECESSED CEILING FRAME HIDDEN PROFILE SILENT I 60X60






Solutions S



Pack

CLASSROOMS Pack

description



luminaire or surface box. Preconfigured for easy operation.

description



Regulation by contribution of natural light and stand alone presence. Lighting control system to meet CTE requirements and optimize energy use by taking advantage of natural light and automatic shutdown in case of absence.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es