Imagine Ip20

470889

PRILUX

Specifications (Series luminaires)

Electrical isolation	CIII
Voltage (V)	24V dcV
Frecuency (Hz)	50-60Hz
IP Tightness index	IP20
Colour temperature	Ámbar
CRI Colour rendering index	>80
Opening angle	120°
Measures	5.000x10mm
Strip cutting unit	100mm
Lifetime	(L70B50>) 50.000h

Imagine Ip20
470889

PRILUX

References

	W	K			
470889	4,8W	Ámbar	>80	100mm	5.000x10mm

Dimensions



Photometry

Info

Until end of stock

On request

Consult options according to Imagine

Accessories

472395

IMAGINE MONOCOLOR RF REGULATOR 5-24V 1X5A



242813

POWER SUPPLY 60W 24VDC LED STRIP



242820

POWER SUPPLY 150W 24VDC LED STRIP



242837

POWER SUPPLY 250W 24VDC LED STRIP

Accessories

473682

POWER SUPPLY
60W 24V IP67
LPV-60-24

473699

POWER SUPPLY
100W 24V IP67
LPV-100-24

473705

POWER SUPPLY
150W 24V IP67
LPV-150-24

473057

CONNECTOR
IMAGINE
MONOCOLOR IP20
CABLE-STRIP

473071

CONNECTOR
IMAGINE
MONOCOLOR IP20
STRIP-STRIP



209151

STRIP CONNECTOR X
IP20 2835 10MM 2P



209144

T-STRIP CONNECTOR
IP20 2835 10MM 2P

501453

POWER SUPPLY
XLG-200-24-A IP67

001662

POWER SUPPLY
DALI LCA 35W 24V
SC PRE

001663

POWER SUPPLY
DALI LCA 60W 24V
SC PRE

001253

POWER SUPPLY
DALI LCA 100W 24V
SC PRE

001437

POWER SUPPLY
DALI LCA 150W 24V
SC PRE

487863

POWER SUPPLY BT
HLC 35 / 24V bDW SC
PRE2

487870

POWER SUPPLY BT
LC 60 / 24V bDW SC
PRE2

487887

POWER SUPPLY BT
LC 100 / 24V bDW SC
PRE2

487894

POWER SUPPLY BT
LC 150 / 24V bDW SC
PRE2