




Specifications (Series luminaires)			
	Electrical isolation	CIII	
	Voltage (V)	24V dcV	
Hz	Frecuency (Hz)	50-60Hz	
	IP Tightness index	IP20	
K	Colour temperature	4.000K	
	CRI Colour rendering index	>90	
	Opening angle	120°	
	Measures	5.000x10mm	
	Strip cutting unit	20mm	
	Lifetime	(L70B50>) 50.000h	

References					
					
	W	K			
471046	24,5W	4.000K	>90	20mm	5.000x10mm

Dimensions	Photometry
	

Info



Until end of stock

On request




Consult options according to Imagine

Accessories




472395

IMAGINE
MONOCOLOR RF
REGULATOR 5-24V
1X5A




242813

POWER SUPPLY
60W 24VDC LED
STRIP



242820

POWER SUPPLY
150W 24VDC LED
STRIP



242837

POWER SUPPLY
250W 24VDC LED
STRIP

Accessories



473682

POWER SUPPLY
60W 24V IP67
LPV-60-24



473699

POWER SUPPLY
100W 24V IP67
LPV-100-24



473705

POWER SUPPLY
150W 24V IP67
LPV-150-24




473057

CONNECTOR
IMAGINE
MONOCOLOR IP20
CABLE-STRIP




473071

CONNECTOR
IMAGINE
MONOCOLOR IP20
STRIP-STRIP



209151

STRIP CONNECTOR X
IP20 2835 10MM 2P



209144

T-STRIP CONNECTOR
IP20 2835 10MM 2P



501453

POWER SUPPLY
XLG-200-24-A IP67



001662

POWER SUPPLY
DALI LCA 35W 24V
SC PRE



001663

POWER SUPPLY
DALI LCA 60W 24V
SC PRE



001253

POWER SUPPLY
DALI LCA 100W 24V
SC PRE



001437

POWER SUPPLY
DALI LCA 150W 24V
SC PRE



487863

POWER SUPPLY BT
HLC 35 / 24V bDW SC
PRE2



487870

POWER SUPPLY BT
LC 60 / 24V bDW SC
PRE2



487887

POWER SUPPLY BT
LC 100 / 24V bDW SC
PRE2



487894

POWER SUPPLY BT
LC 150 / 24V bDW SC
PRE2