




Specifications (Series luminaires)

	Electrical isolation	CIII
	Voltage (V)	24V dcV
Hz	Frecuency (Hz)	50-60Hz
	IP Tightness index	IP20
K	Colour temperature	2.700K~6.500K
	CRI Colour rendering index	>90
	Opening angle	120°
	Measures	2.000x10mm
	Strip cutting unit	50mm
	Lifetime	(L70B50>) 50.000h

References					
					
	W	K			
471077	19,2W	2.700K~6.500K	>90	50mm	2.000x10mm

Dimensions	Photometry
	

Info



Until end of stock

On request



Consult options according to Imagine

Accessories




472401

IMAGINE DUAL RF
REGULATOR 5-24V
2X5A




472432

IMAGINE DUAL
AMPLIFIER 5-24V
2X5A



242813


POWER SUPPLY
60W 24VDC LED
STRIP



242820

POWER SUPPLY
150W 24VDC LED
STRIP

Accessories



242837

POWER SUPPLY
250W 24VDC LED
STRIP



473682

POWER SUPPLY
60W 24V IP67
LPV-60-24



473699

POWER SUPPLY
100W 24V IP67
LPV-100-24



473705

POWER SUPPLY
150W 24V IP67
LPV-150-24



501453

POWER SUPPLY
XLG-200-24-A IP67