


















Specifications			
	Voltage (V)	24V dc	
	Frecuency (Hz)	50-60	
	Colour temperature	RGBW	
	Opening angle	120°	
	Measures	5x12	
	Electrical isolation	III	
	Lifetime	(L70B50>) 50.000h	

References					
	W	K			
471350	19,2W	RGBW	100mm	5x12	

Dimensions 	Photometry 
	

Info



>10m less performance (7,2W/m-14,4W/m). >5m less performance (19,2W/m). The life time of our LED strips is 50,000h as long as the ambient temperature does not exceed 25 °C. To ensure the life of the LED for our strips ≥ 9.6W, it is mandatory to place it on a surface that dissipates the heat they generate.

## Accessories




**472425**

IMAGINE RGBW  
CONTROLLER 5-24V  
3X2.5A+4A




**472456**

IMAGINE RGBW  
AMPLIFIER 5-24V  
3X3A+5A




**242813**

POWER SUPPLY  
60W 24VDC LED  
STRIP



**242820**

POWER SUPPLY  
150W 24VDC LED  
STRIP



**242837**

POWER SUPPLY  
250W 24VDC LED  
STRIP



**473682**

POWER SUPPLY  
60W 24V IP67  
LPV-60-24



**473699**

POWER SUPPLY  
100W 24V IP67  
LPV-100-24



**473705**

POWER SUPPLY  
150W 24V IP67  
LPV-150-24



**473156**

CONNECTOR  
IMAGINE RGBW IP20  
CABLE-STRIP



**473170**

CONNECTOR  
IMAGINE RGBW IP20  
STRIP-STRIP



**501453**

POWER SUPPLY  
XLG-200-24-A IP67