














## Specifications (Series luminaires)




	<b>Electrical isolation</b>	CIII
	<b>Voltage (V)</b>	24V dcV
	<b>Frecuency (Hz)</b>	50-60Hz
<hr/>		
	<b>Colour temperature</b>	RGB
	<b>Opening angle</b>	120°
<hr/>		
	<b>Measures</b>	5.000x10mm
	<b>Strip cutting unit</b>	165mm
<hr/>		
	<b>Lifetime</b>	(L70B50>) 50.000h

## References

	W	K		
<b>471367</b>	7,2W	RGB	165mm	5.000x10mm

## Dimensions



## Photometry

### Info

>10m less performance (7,2W/m-14,4W/m). >5m less performance (19,2W/m). The life time of our LED strips is 50,000h as long as the ambient temperature does not exceed 25 °C. To ensure the life of the LED for our strips  $\geq 9.6W$ , it is mandatory to place it on a surface that dissipates the heat they generate.

## Accessories



**472418**

IMAGINE RGB RF  
CONTROLLER 5-24V  
3X4A



**472449**

IMAGINE RGB  
AMPLIFIER 5-24V  
3X4A



**473682**

POWER SUPPLY  
60W 24V IP67  
LPV-60-24



**473699**

POWER SUPPLY  
100W 24V IP67  
LPV-100-24




**473705**

POWER SUPPLY  
150W 24V IP67  
LPV-150-24




**473101**

CONNECTOR  
IMAGINE RGB IP65  
CABLE-STRIP




**473125**

CONNECTOR  
IMAGINE RGB IP65  
STRIP-STRIP



**209182**

STRIP CONNECTOR X  
IP20 5050 RGB 10MM  
4P



**209175**

T-STRIP CONNECTOR  
IP20 5050 RGB 10MM  
4P



**501453**

POWER SUPPLY  
XLG-200-24-A IP67

## Info



Quick connector. Fastening clip. Serial connection: 18W:  
32luminaires 37W: 20luminaires 57W: 13luminaires