



Specifications (Series luminaires)

	Electrical isolation	CIII
	Voltage (V)	24V dcV
	Frecuency (Hz)	50-60Hz
	Colour temperature	RGB
	Opening angle	120°
	Measures	5.000x10mm
	Strip cutting unit	100mm
	Lifetime	(L70B50>) 50.000h

References					
	W	K			
471374	14,4W	RGB	100mm	5.000x10mm	

Dimensions		Photometry	
------------	--	------------	--

Info



>10m less performance (7,2W/m-14,4W/m). >5m less performance (19,2W/m). The life time of our LED strips is 50,000h as long as the ambient temperature does not exceed 25 °C. To ensure the life of the LED for our strips ≥ 9.6W, it is mandatory to place it on a surface that dissipates the heat they generate.

Accessories



472418

IMAGINE RGB RF
CONTROLLER 5-24V
3X4A



472449

IMAGINE RGB
AMPLIFIER 5-24V
3X4A



473682

POWER SUPPLY
60W 24V IP67
LPV-60-24



473699

POWER SUPPLY
100W 24V IP67
LPV-100-24




473705

POWER SUPPLY
150W 24V IP67
LPV-150-24




473101

CONNECTOR
IMAGINE RGB IP65
CABLE-STRIP




473125

CONNECTOR
IMAGINE RGB IP65
STRIP-STRIP



209182

STRIP CONNECTOR X
IP20 5050 RGB 10MM
4P



209175

T-STRIP CONNECTOR
IP20 5050 RGB 10MM
4P



501453

POWER SUPPLY
XLG-200-24-A IP67

Info



Quick connector. Fastening clip. Serial connection: 18W: 32luminaires 37W: 20luminaires 57W: 13luminaires