














Specifications (Series luminaires)




	Electrical isolation	CIII
	Voltage (V)	24V dcV
	Frecuency (Hz)	50-60Hz
	Colour temperature	RGBW
	Opening angle	120°
	Measures	5.000x12mm
	Strip cutting unit	100mm
	Lifetime	(L70B50>) 50.000h

References

	W	K		
471381	19,2W	RGBW	100mm	5.000x12mm

Dimensions



Photometry



Info



>10m less performance (7,2W/m-14,4W/m). >5m less performance (19,2W/m). The life time of our LED strips is 50,000h as long as the ambient temperature does not exceed 25 °C. To ensure the life of the LED for our strips $\geq 9.6W$, it is mandatory to place it on a surface that dissipates the heat they generate.

Accessories



472425

IMAGINE RGBW
CONTROLLER 5-24V
3X2.5A+4A



472456

IMAGINE RGBW
AMPLIFIER 5-24V
3X3A+5A



473682

POWER SUPPLY
60W 24V IP67
LPV-60-24



473699

POWER SUPPLY
100W 24V IP67
LPV-100-24




473705

POWER SUPPLY
150W 24V IP67
LPV-150-24



473149

CONNECTOR
IMAGINE RGBW IP65
CABLE-STRIP



473163

CONNECTOR
IMAGINE RGBW IP65
STRIP-STRIP



501453

POWER SUPPLY
XLG-200-24-A IP67

Info



Quick connector. Fastening clip. Serial connection: 18W: 32luminaires 37W: 20luminaires 57W: 13luminaires