Breno Sq
483131

PRILUX



Specifications (Series luminaires)

Electrical isolation	CII
Voltage (V)	230V
Frecuency (Hz)	50/60Hz
Power factor (Cos fi)	≥0,9
Dimming	No
IP Tightness index	IP20
IP installed Sealing rating	IP40
Diffuser Material	PC-O
Body	AL
Colour temperature	3000K
CRI Colour rendering index	>80
Opening angle	120°
Measures	170x170x18mm
Operating temperature	-
Flux (lm)	929lm
Guarantee	3garantia
Lifetime	(L70B50>)35.000H


Breno Sq
483131

PRILUX

References

	W	LUM	K				
483131	12W	929lm	3000K	>80		170x170x18mm	No

Dimensions



Photometry

Solutions

CTE Pack

description

Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.

CLASSROOMS Pack

description

Regulation by contribution of natural light and stand alone presence. Lighting control system to meet CTE requirements and optimize energy use by taking advantage of natural light and automatic shutdown in case of absence.

BLUETOOTH Pack

description

Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

You need

description

Need DALI driver

You need

description

Info

For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es