



Specifications (Series luminaires)							
1							
\$	Voltage (V)	220-240V					
Hz	Frecuency (Hz)	50/60Hz					
φ	Power factor (Cos fi)	≥0,9					
	Dimming	Yes					
0 0	IP Tightness index	IP20					
00	Body color	White					
11/	Diffuser Material	РММА-Р					
	Body	FE					
K	Colour temperature	4000K					
Å	CRI Colour rendering index	>80					
$ \Longleftrightarrow $	Measures	1.200x300x1.200m					
←	Mounting position	Empotrado Techo					
Atc	Operating temperature	-					
\$LUM	Flux (lm)	4,026lm					
		·					
	Electrical isolation	CII					
		•					
	Lifetime	(L70B50>)50.000h					
	Lifetime	(L70B50>)50.000h					

Silent Led I Ugr




References											
	₩	W		φ	$\Phi_{\scriptscriptstyle{LED}}$	ф	K	\bigcirc			
483933	36W	40W	1000mA	≥0,9	4953lm	4026lm	4000K	Yes			

Dimensions



Photometry







Silent Led I Ugr



Accessories $\langle \bigcirc \rangle$



964562

FRAME WH RECESSED PLASTER SILENT LED 60X60CM



207591

FRAME BL RECESS PLASTER SILENT LED 120X30CM



164092

WH SURFACE DRAWER SILENT LED 60X60CM



207874

WH SURFACE **DRAWER SILENT** LED 120X30CM



397391

RECESSED CEILING FRAME HIDDEN PROFILE SILENT I 60X60



384070

WH FRAME RECESS PLASTER SILENT LED 120X60CM



383806

WH SURFACE DRAWER SILENT LED 120X60CM



484039

WH SURFACE DRAWER SILENT LED I 30X120X4,8CM DES

Silent Led I Ugr



Solutions S



CTE Pack

BLUETOOTH Pack

description



Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.

description



Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es