




Specifications (Series lumin	aires)			
4 Voltage (V)	220-240V	<u></u>	Measures	Ø145x81,8m
HZ Frecuency (Hz)	50-60Hz		Mounting position	Empotrar
Current (A)	700mA	<u> </u>		
Dimming	No	ф_	Flux (lm)	1.182/1.249lm
© IP Tightness index	IP20		Electrical isolation	CII
K Impact resistance	IKO			-
① Body color	White		Lifetime	L70>40.000
9 Diffuser Material	AL-AN			·
☐ Body	AL			
K Colour temperature	3.000K/4.000K			
CRI Colour rendering index	>80	_		
UGR	UGR <19			

Prilux guarantees a ± 10% tolerance in light flux measurements.

Dimensions






References	5							
	W _{LED}	W		$\Phi_{ t LED}$	Ф	\triangle	K	\longleftrightarrow
492652	12W	15W	700mA	1.427/1.561lm	1.182/1.249lm	50°	3.000K/4.000K Ø145x81,8mm	



Photometry





On request







Bluetooth

Emergency kit



Solutions S



CTE Pack



description



Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.

description



Regulation by contribution of natural light and stand alone presence. Lighting control system to meet CTE requirements and optimize energy use by taking advantage of natural light and automatic shutdown in case of absence.

Bluetooth package

description



Casambi version of our fixtures that enables through any Bluetooth® terminal via free APP that offers the control of flow regulation, color,scene configuration, behavior linked to schedules. Multiple accessories can be configured to work onthe same network to unify the control of one ormore spaces, being able to create groups, scenes and dynamic sequences to measure. The Bluetooth® device is valid for any DALI luminaire.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es



Info	(j
You need DALI drive	