






















Specifications (Series luminaires)

| | | |
|---|-----------------------------------|----------------------|
|  | Voltage (V) | 230V |
| Hz | Frecuency (Hz) | 50-60Hz |
|  | Dimming | No |
|  | IP Tightness index | IP20 |
|  | Body color | White |
|  | Body | AL |
| K | Colour temperature | 3.000K,4.000K |
|  | CRI Colour rendering index | >80 |
|  | Optical | PC |
|  | Opening angle | 90° |
|  | UGR | <19 |
|  | Measures | 595x595x14,5mm |
|  | Mounting position | Empotrar |
|  | Operating temperature | -5°C~+35 °C |
|  | Flux (lm) | 3.725/4.164lm |
|  | Electrical isolation | CII |
|  | Lifetime | (L70B50>) 50.000h |

References




|  | W _{LED} | W |  | ϕ_{LED} | ϕ_{LUM} | K |  |  |
|---|------------------|-----|---|---------------|---------------|---------------|---|---|
| 496360 | 35W | 32W | 850mA | 4.678/4.986lm | 3.725/4.164lm | 3.000K,4.000K | 575 x 575 | No |

Dimensions



Photometry





On request



Emergency kit 1h



Dali

Bluetooth

Accessories



964562

FRAME WH
RECESSED PLASTER
SILENT LED 60X60CM



164092

WH SURFACE
DRAWER SILENT
LED 60X60CM



491532

DIANE TECH
SUSPENSION KIT 1,5M



Solutions

S



CTE Pack

description



Regulation for the contribution of natural light to comply with the requirements of the CTE. Independent control of two lines of dimmable DALI luminaires with sensor to install in a luminaire or surface box. Preconfigured for easy operation.



CLASSROOMS Pack

description



Regulation by contribution of natural light and stand alone presence. Lighting control system to meet CTE requirements and optimize energy use by taking advantage of natural light and automatic shutdown in case of absence.



BLUETOOTH Pack

description



Device that enables DALI luminaire control through any Bluetooth® terminal via free APP that offers us control of flow regulation, color, scene configuration, behavior linked to schedules.

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es