



MADE IN SPAIN
Design by PRILUX



Applications



Sports grounds



Industrial Zones



Signage










Certifications











Specifications



	Voltage (V)	220-240
Hz	Frecuency (Hz)	50-60
	Current (A)	10.200mA
	LED number	576
	Dimming	DALI
	IP Tightness index	66
	Diffuser Material	VT
	Body	AL iap
K	Colour temperature	4.000K
	CRI Colour rendering index	>70
	Optical	HEMA576-S060L2P

	Measures	974x463x366
	Operating temperature	-30~+35°C
	Surges protection	Si
	Flux (lm)	187.94
	Electrical isolation	CI
	Lifetime	L90B10>200.000h









Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions




References



		W	W				ϕ/W			
499828	4X	1.400	1.520	10.200mA	219.4	187.94	124W	576	HEMA576-S060L2P	Yes

Photometry



On request



PC-T (IK10)

S020I2P

S090I2P

K

>70 3.000K

>80 3.000K



Technologies



Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

SystemShield



SYSTEMSHIELD technology is designed to guarantee the hours of useful life of luminaires installed in environments where exceeding the maximum operating temperature is possible and even probable. Using thermal probes, the luminaire knows its operating temperature at all times.

Rules



Threephase electrified rail and accessories in white, black and grey. Adapter for three phase track 250V 6A.

Warning



You need DALI drive



Cora Sport

description

CORA SPORTS is the family of devices by Priluxto control DALI light fixtures in new or existing installations, indoors or outdoors, using Bluetooth5.0 wireless technology. Technology that is more efficient and easier to deploy and scale for professional lighting applications. It can work in a meshed arrangement with the light fixtures and to create smart communication networks. Especially recommended in installations with towers and/or groups of light fixtures to make it possible to operate them as a group or individually.

Info

For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.grupoprilux.com