



MADE IN SPAIN  
Design by PRILUX




### Applications



Sports grounds



Industrial Zones



Signage










### Certifications











## Specifications



	<b>Voltage (V)</b>	220-240
Hz	<b>Frecuency (Hz)</b>	50-60
	<b>Current (A)</b>	10.200mA
	<b>LED number</b>	576
	<b>Dimming</b>	DALI
	<b>IP Tightness index</b>	66
	<b>Diffuser Material</b>	VT
	<b>Body</b>	AL iap
K	<b>Colour temperature</b>	5.000K
	<b>CRI Colour rendering index</b>	>70
	<b>Optical</b>	HEMA576-S030L2P

	<b>Measures</b>	974x463x366
	<b>Operating temperature</b>	-30~+35°C
	<b>Surges protection</b>	Si
	<b>Flux (lm)</b>	188.713
	<b>Electrical isolation</b>	CI
	<b>Lifetime</b>	L90B10>200.000h









Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.

## Dimensions




## References



		W	W				$\phi/W$			
499842	4X	1.400	1.520	10.200mA	219.4	188.713	124W	576	HEMA576-S030L2P	Yes

## Photometry



## On request



PC-T (IK10)

S020I2P

S090I2P

K

>70 3.000K

>80 3.000K



## Technologies



### Overstorm



OVERSTORM technology is designed for those luminaires that normally face electrically aggressive environments. It provides the product with three spheres of protection: In the outer sphere, an independent surge protector suppresses eventual voltage surges, in the intermediate sphere the drivers are prepared to withstand voltage peaks of up to 6 kV and 10kV. In the nuclear sphere, the protection in the LED module is provided both at its input, for small surges that have not been filtered by the external spheres.

### SystemShield



SYSTEMSHIELD technology is designed to guarantee the hours of useful life of luminaires installed in environments where exceeding the maximum operating temperature is possible and even probable. Using thermal probes, the luminaire knows its operating temperature at all times.

### Rules



Threephase electrified rail and accessories in white, black and grey. Adapter for three phase track 250V 6A.

### Warning



You need DALI drive



## Cora Sport

### description

CORA SPORTS is the family of devices by Prilux to control DALI light fixtures in new or existing installations, indoors or outdoors, using Bluetooth 5.0 wireless technology. Technology that is more efficient and easier to deploy and scale for professional lighting applications. It can work in a meshed arrangement with the light fixtures and to create smart communication networks. Especially recommended in installations with towers and/or groups of light fixtures to make it possible to operate them as a group or individually.

### Info

For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web [www.grupoprilux.com](http://www.grupoprilux.com)