







## Specifications (Series luminaires)




	<b>Electrical isolation</b>	CIII
	<b>Voltage (V)</b>	24V dcV
	<b>Frecuency (Hz)</b>	50-60Hz
<hr/>		
	<b>IP Tightness index</b>	IP65
<hr/>		
	<b>Colour temperature</b>	2700k
	<b>CRI Colour rendering index</b>	>80
	<b>Opening angle</b>	120°
<hr/>		
	<b>Measures</b>	30.000x10mm
	<b>Strip cutting unit</b>	50mm
<hr/>		
	<b>Lifetime</b>	L70B50>) 50.000h

## References

	W	K			
502719	14,4W	2700k	>80	50mm	30.000x10mm

## Dimensions



## Photometry



## Info



Loss of intensity for more than 10m. The useful life of our led strips is 50,000h as long as the temperature ambient temperature does not exceed 25 ° C. Mandatory placement of strips on surfaces that dissipate heat that they generate in order to guarantee the life of the led,

## Accessories



**472395**

IMAGINE  
MONOCOLOR RF  
REGULATOR 5-24V  
1X5A



**473682**

POWER SUPPLY  
60W 24V IP67  
LPV-60-24



**473699**

POWER SUPPLY  
100W 24V IP67  
LPV-100-24



**473705**

POWER SUPPLY  
150W 24V IP67  
LPV-150-24




**473040**

CONNECTOR  
IMAGINE  
MONOCOLOR IP65  
CABLE-STRIP



**473064**

CONNECTOR  
IMAGINE  
MONOCOLOR IP65  
STRIP-STRIP



**209151**

STRIP CONNECTOR X  
IP20 2835 10MM 2P



**209144**

T-STRIP CONNECTOR  
IP20 2835 10MM 2P



**501453**

POWER SUPPLY  
XLG-200-24-A IP67



**001662**

POWER SUPPLY  
DALI LCA 35W 24V  
SC PRE



**001663**

POWER SUPPLY  
DALI LCA 60W 24V  
SC PRE



**001253**

POWER SUPPLY  
DALI LCA 100W 24V  
SC PRE

## Accessories



**001437**

POWER SUPPLY  
DALI LCA 150W 24V  
SC PRE



**487863**

POWER SUPPLY BT  
HLC 35 / 24V bDW SC  
PRE2



**487870**

POWER SUPPLY BT  
LC 60 / 24V bDW SC  
PRE2



**487887**

POWER SUPPLY BT  
LC 100 / 24V bDW SC  
PRE2



**487894**

POWER SUPPLY BT  
LC 150 / 24V bDW SC  
PRE2