

















## Specifications (Series luminaires)




	<b>Electrical isolation</b>	CIII
	<b>Voltage (V)</b>	24V dcV
	<b>Frecuency (Hz)</b>	50-60Hz
<hr/>		
	<b>IP Tightness index</b>	IP65
<hr/>		
	<b>Colour temperature</b>	RGB
	<b>CRI Colour rendering index</b>	>80
	<b>Opening angle</b>	120°
<hr/>		
	<b>Measures</b>	30.000x10mm
	<b>Strip cutting unit</b>	50mm
<hr/>		
	<b>Lifetime</b>	(L70B50>) 50.000h

## References

	W	K			
502764	14,4W	RGB	>80	50mm	30.000x10mm

## Dimensions



## Photometry



## Info



Loss of intensity for more than 10m. The useful life of our led strips is 50,000h as long as the temperature ambient temperature does not exceed 25 ° C. Mandatory placement of strips on surfaces that dissipate heat that they generate in order to guarantee the life of the led,

## Accessories



**472418**

IMAGINE RGB RF  
CONTROLLER 5-24V  
3X4A



**472449**

IMAGINE RGB  
AMPLIFIER 5-24V  
3X4A



**473682**

POWER SUPPLY  
60W 24V IP67  
LPV-60-24



**473699**

POWER SUPPLY  
100W 24V IP67  
LPV-100-24



**473705**

POWER SUPPLY  
150W 24V IP67  
LPV-150-24




**473101**

CONNECTOR  
IMAGINE RGB IP65  
CABLE-STRIP




**473125**

CONNECTOR  
IMAGINE RGB IP65  
STRIP-STRIP



**209182**

STRIP CONNECTOR X  
IP20 5050 RGB 10MM  
4P



**209175**

T-STRIP CONNECTOR  
IP20 5050 RGB 10MM  
4P



**501453**

POWER SUPPLY  
XLG-200-24-A IP67