

MADE IN SPAIN
Design by PRILUX



Applications




Facades



Industrial Zones



Industrial



Sports grounds



Monuments



Car parks

Certifications



Specifications (Series luminaires)

	Voltage (V)	-V
Hz	Frecuency (Hz)	-Hz
ϕ	Power factor (Cos fi)	-
	Dimming	No
	Comm. Prot. for reprogr.	-

	Optical	-
	Higher Hemispheric Flow	-lm

	Measures	0mm
	Wind Resistance	-
	Inclination	-

	Operating temperature	-
---	------------------------------	---

	Surges protection	No
---	--------------------------	----


ϕ_{LUM}	Flux (lm)	-lm
	Performance	-

	Electrical isolation	C-
--	-----------------------------	----

	Lifetime	-
---	-----------------	---

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

	W_{LED}	W	ϕ	ϕ_{LED}	ϕ_{LUM}	ϕ/W		
515832	-	-W	-lm	-lm	-lm	-	-	No

Light packages

			PCA	722	727	730	827	830	840
W			ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W
NaNW	0	0mA	0lm 0lm/W	0lm 0lm/W	0lm 0lm/W	0lm 0lm/W	0lm	0lm 0lm/W	0lm 0lm/W