

MADE IN SPAIN
Design by PRILUX



Applications




Facades



Industrial




Car parks



Sports grounds



Monuments



Industrial Zones

Certifications




Specifications (Series luminaires)

	Voltage (V)	220-240V
Hz	Frequency (Hz)	50/60Hz
	Current (A)	500mA
ϕ	Power factor (Cos fi)	0.96
	LED number	108
	Dimming	No
	IP Tightness index	IP66
	IK Impact resistance	IK09
	Body color	9007
	Body	AL iap
K	Colour temperature	4000K
	CRI Colour rendering index	>70
	Optical	S090I2P

	Measures	250x55x438mm
	Weight	0.00575Kg
	Wind Resistance	0,11m2
	Operating temperature	-30°C ~ +50°C
	Surges protection	No
	Flux (lm)	9,374lm
	Electrical isolation	CI
	Lifetime	L70B10>100.000h

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.


Dimensions



References

				ϕ	ϕ_{LED}	ϕ_{LUM}	ϕ/W			
519847	51W	55,1W	500mA	10900lm	10775lm	9374lm	170lm/W	108	S090I2P	No

Photometry



Light packages



			PCA	722	727	730	827	830	840
W			ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W	ϕ_{LUM} ϕ/W
55,1W	108	500mA					7.365lm 134lm/W	7.700lm 140lm/W	8.369lm 152lm/W

Accessories



515788

ACCESSORY
PARALUMEN
NANTES RAL9005T

Solutions

S



Cora Manager

description



Lighting management in the electrical panel that allows group control of the luminaires connected to the control center via the power line (CMR) without additional wiring

Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.prilux.es