

**MADE IN SPAIN**  
Design by PRILUX



---

## Applications

---



Industry/Logistics












Covered car parks








Large surfaces

## Specifications (Series luminaires)




	<b>Voltage (V)</b>	220-240V
Hz	<b>Frecuency (Hz)</b>	50-60Hz
	<b>Current (A)</b>	500mA
$\phi$	<b>Power factor (Cos fi)</b>	0.92
	<b>LED number</b>	72
	<b>Dimming</b>	No
	<b>IP Tightness index</b>	IP66
	<b>IK Impact resistance</b>	IK10
	<b>Diffuser Material</b>	PC-O
	<b>Body</b>	PC
K	<b>Colour temperature</b>	4.000K
	<b>CRI Colour rendering index</b>	>80

	<b>Measures</b>	0mm
	<b>Weight</b>	1.2Kg
	<b>Mounting</b>	Superficie
	<b>Operating temperature</b>	-20~+35°C
$\phi_{LUM}$	<b>Flux (lm)</b>	2674lm
	<b>Electrical isolation</b>	CI






Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.

## Dimensions



## References



		$W_{LED}$	W		$\phi_{LED}$	$\phi_{LUM}$	$\phi/W$		K	
524896	1X	16W	20,1W	500mA	3128lm	2674lm	133lm/W	72	4.000K	>80

---

**On request**

---



Dali

---