



**MADE IN SPAIN**  
Design by PRILUX



---

## Applications

---



Industry/Logistics

















Covered car parks



Large surfaces


## Specifications (Series luminaires)

|  |                                   |          |
|--|-----------------------------------|----------|
|    | <b>Voltage (V)</b>                | 220-240V |
| Hz   | <b>Frecuency (Hz)</b>             | 50-60Hz  |
|    | <b>Current (A)</b>                | 300mA    |
| $\phi$   | <b>Power factor (Cos fi)</b>      | 0.91     |
|    | <b>LED number</b>                 | 144      |
|    | <b>Dimming</b>                    | No       |
|    | <b>IP Tightness index</b>         | IP66     |
|    | <b>IK Impact resistance</b>       | IK10     |
|    | <b>Diffuser Material</b>          | PC-O     |
|    | <b>Body</b>                       | PC       |
| K  | <b>Colour temperature</b>         | 4.000K   |
|  | <b>CRI Colour rendering index</b> | >80      |






|   |                              |            |
|---|------------------------------|------------|
|  | <b>Measures</b>              | 0mm        |
|  | <b>Weight</b>                | 1.8Kg      |
|  | <b>Mounting</b>              | Superficie |
|  | <b>Operating temperature</b> | -20~+45°C  |
| $\phi_{LUM}$  | <b>Flux (lm)</b>             | 3244lm     |
|  | <b>Electrical isolation</b>  | CI         |

Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.

## Dimensions



## References

|   |   |           |       |   |              |              |          |   |        |   |
|---|---|-----------|-------|---|--------------|--------------|----------|---|--------|---|
|  |  | $W_{LED}$ | W     |  | $\phi_{LED}$ | $\phi_{LUM}$ | $\phi/W$ |  | K      |  |
| 524926  | 1X  | 19W       | 22,3W | 300mA   | 3816lm       | 3244lm       | 145lm/W  | 144   | 4.000K | >80   |

---

**On request**

---



Dali

---