

MADE IN SPAIN
Design by PRILUX



Applications



Industry/Logistics



Covered car parks











Large surfaces







Certifications



Specifications (Series luminaires)




	Voltage (V)	220-240V
Hz	Frecuency (Hz)	50-60Hz
	Current (A)	300mA
ϕ	Power factor (Cos fi)	0.91
	LED number	144
	Dimming	No
	IP Tightness index	IP66
	IK Impact resistance	IK10
	Body color	Light grey
	Diffuser Material	PC-O
	Body	PC
K	Colour temperature	4.000K
	CRI Colour rendering index	>80

	Measures	1.265x82x87mm
	Weight	1.8Kg
	Mounting	Superficie
	Operating temperature	-20°C
ϕ_{LUM}	Flux (lm)	3.244lm
	Electrical isolation	CCI
	Lifetime	L90B10>200000h






Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References



	W_{LED}	W		ϕ_{LED}	ϕ_{LUM}	ϕ/W		K		
524926	1x19	22,3W	300mA	3.816lm	3.244lm	145lm/W	144	4.000K	>80	1.265x82x87mm

On request



Emergency kit 3h (mod. 1x/2x
1.200mm/1.500mm)
Cableado Pasante



Dali

K

>80 4.000K



Presence and brightness sensor (mod.
1x/2x 1.200mm/1.500mm)