



**MADE IN SPAIN**  
Design by PRILUX



---

## Applications

---



Industry/Logistics

















Covered car parks



Large surfaces


## Specifications (Series luminaires)

	<b>Voltage (V)</b>	220-240V
Hz	<b>Frecuency (Hz)</b>	50-60Hz
	<b>Current (A)</b>	800mA
$\phi$	<b>Power factor (Cos fi)</b>	0.96
	<b>LED number</b>	180
	<b>Dimming</b>	No
	<b>IP Tightness index</b>	IP66
	<b>IK Impact resistance</b>	IK10
	<b>Diffuser Material</b>	PC-O
	<b>Body</b>	PC
K	<b>Colour temperature</b>	4.000K
	<b>CRI Colour rendering index</b>	>80






	<b>Measures</b>	0mm
	<b>Weight</b>	2.2Kg
	<b>Mounting</b>	Superficie
	<b>Operating temperature</b>	-20~+45°C
$\phi_{LUM}$	<b>Flux (lm)</b>	9884lm
	<b>Electrical isolation</b>	CI

Prilux guarantees a  $\pm 10\%$  tolerance in light flux measurements.

## Dimensions




## References

		$W_{LED}$	W		$\phi_{LED}$	$\phi_{LUM}$	$\phi/W$		K	
524988	1X	65W	73,1W	800mA	11621lm	9884lm	135lm/W	180	4.000K	>80

---

**On request**

---



Dali

---