



MADE IN SPAIN
Design by PRILUX



Applications



Industry/Logistics

















Covered car parks




Large surfaces

Specifications (Series luminaires)






| | | | |
|--|----------|--|------------|
|  Voltage (V) | 220-240V |  Measures | 0mm |
| Hz Frequency (Hz) | 50-60Hz |  Weight | 2.2Kg |
|  Current (A) | 550mA |  Mounting | Superficie |
| ϕ Power factor (Cos fi) | 0.95 | | |
|  LED number | 180 |  Operating temperature | -20~+35°C |
|  Dimming | No | | |
| | | ϕ_{LUM} Flux (lm) | 7219lm |
|  IP Tightness index | IP66 | | |
|  IK Impact resistance | IK10 |  Electrical isolation | CI |
|  Diffuser Material | PC-O | | |
|  Body | PC | | |
| | | | |
| K Colour temperature | 5.000K | | |
|  CRI Colour rendering index | >80 | | |

Prilux guarantees a $\pm 10\%$ tolerance in light flux measurements.

Dimensions



References

| | | | | | | | | | | |
|---|---|-----------|-------|---|--------------|--------------|----------|---|----------|---|
|  |  | W_{LED} | W |  | ϕ_{LED} | ϕ_{LUM} | ϕ/W |  | K |  |
| 525169 | 1X | 45W | 50,4W | 550mA | 8493lm | 7219lm | 143lm/W | 180 | 5.000K | >80 |

On request



Dali
